

Dixon™ Hydrant Gate Valves with Speed Handle



Application:

- protects fire hydrants from damage that can occur if they are used for throttling

Features:

- full 2½" waterway
- anodized throughout - minimum thickness 0.001"
- test pressure: **250 PSI**, working pressure: **100 PSI** at 70°F (21°C)

Inlet Female Swivel	Outlet Male	Aluminum Alloy, 356-T6 Part #	Price
2½" NPSH	2½" NPSH	AHGV250	\$656.25
2½" NST (NH)	2½" NST (NH)	AHGV250F	656.25

Replacement Parts



handwheel and knob

Description	Part #	Price
handwheel and knob	HGV-HDWHL	\$48.00
knob only	HGV-KNOB	14.00

Global Hydrant Gate Valves with Speed Handle



Application:

- protects fire hydrants from damage that can occur if they are used for throttling

Features:

- pin lug swivel, non-rising stem, aluminum speed handle
- non-metallic seal
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)

Inlet Female NST (NH)	Outlet Male NST (NH)	Aluminum Part #	Price
2½"	2½"	AHGV250F-I	\$394.30

Replacement Part



Description	Aluminum Part #	Price
speed handle	AHGV250F-H	\$68.75

P