## $\mathsf{Dixon}^{\scriptscriptstyle{\mathsf{TM}}}$ / $\mathsf{Boss\text{-}Lock}^{\scriptscriptstyle{\mathsf{TM}}}$ Type F Adapters

## male NPT x male adapter



• Pressure rating is based on the seal of the mating part. See ratings on page 32.







356T6 aluminum

aluminum hard coat

brass

33010 aluminum		aluminum naru coat			มเสออ	
Size	356T6 Aluminum		Aluminum Hard Coat		Brass	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	50-F-AL	\$11.00			50-F-BR	\$23.15
3/4" X 1/2"	7550-F-AL	24.00			7550-F-BR	55.50
3/4"	75-F-AL	12.30			75-F-BR	28.10
1"	100-F-AL	15.95			100-F-BR	36.10
11/4"	125-F-AL	19.15			125-F-BR	54.25
1½"	150-F-AL	19.90	150-F-ALH	\$34.10	150-F-BR	47.45
2"	200-F-AL	21.10	200-F-ALH	38.30	200-F-BR	57.30
21/2"	250-F-AL	38.30			250-F-BR	132.50
3"	300-F-AL	38.25	300-F-ALH	62.90	300-F-BR	152.00
4"	400-F-AL	72.50	400-F-ALH	109.00	400-F-BR	218.00
5"	500-F-AL	133.00				
6"	600-F-AL	149.00	600-F-ALH	220.45	600-F-BR	585.00
8" DIX	800-F-AL 1	450.00				
8" BL	801-F-AL <sup>1</sup>	460.00				



 $^1$  Dixon<sup>TM</sup> and Boss-Lock<sup>TM</sup> cam and groove couplings do not interchange in the  $\frac{1}{2}$ " and 8" sizes.







plated malleable iron



316 stainless

unplated malleable Iron		plated malleable Iron			3 to stainless	
Size	Unplated Malleable Iron		Plated Malleable Iron		316 Stainless Steel	
Size	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"					50-F-SS	\$48.40
3/4" X 1/2"					7550-F-SS	73.00
3/4"			75-F-PM	\$24.75	75-F-SS	55.30
1"			100-F-PM	22.80	100-F-SS	60.75
11/4"					125-F-SS	84.70
1½"	150-F-MI	\$33.10	150-F-PM	35.25	150-F-SS	79.30
2"	200-F-MI	38.75	200-F-PM	43.40	200-F-SS	83.00
2½"					250-F-SS	285.00
3"	300-F-MI	73.25	300-F-PM	76.00	300-F-SS	180.00
4"	400-F-MI	108.00	400-F-PM	113.20	400-F-SS	292.30
6"			600-F-PM	275.00	600-F-SS	415.80