
DUPONT™ TYCHEM® 2000 QC125B YL

GARMENT TECHNICAL DATA SHEET



This picture is for measurement reference only.

Customer Service:

United States 1-800-931-3456

Canada 1-800-387-9326

SafeSpec Home Page

Seams and closures have less barrier than fabric. Note: for protection from hazardous or infectious liquids, additional barrier tests are required to establish suitability for use. CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures may provide less barrier than the fabric. If the fabric becomes torn, abraded, or punctured, end-user should discontinue use of garment to avoid compromising the barrier protection. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTES, EXPRESSED OR MIPLIED, INCLUDING WITHOUT LIMITATION NO WARRANTES OF MERCHANTABLITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONVECTION WITH ANY OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infinge any patent, trademark or technical information of DuPont or others covering any material or its use. Data presented does not comprise a product specification.

Warning: Cleanroom apparel should not be used around heat, flames, sparks or in potentially flammable or explosive environments. Cleanroom fabrics should have slipering could and the outer sole of boots, shoe covers, or other gament surfaces in conditions where slipping could occur.

Silicone Statement: In the past, DuPont has found that threads and zippers can be the most significant source of silicone oil contamination in garments. DuPont specifies that thread and zippers used in DuPont^{*M} Tyvek® IsoClean® and ProClean® garments be manufactured without the use of silicone oils. For end uses with concerns about contamination with silicone oils or any other contaminants, the best practice is to audit inbound materials, including garments, for those contaminants.

Latex Statement: As of January 1, 2006, DuPont production specifications exclude use of components containing natural rubber latex in the manufacture of DuPontTM Tyvek® (soClean® and ProClean® garments. Anyone who begins to exhibit allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at 1.800.441.3637.

Measurements are approximate values intended to assist in proper size selection. Normal variability may result in slight differences in actual garment sizes.

Copyright © 2013 DuPont. All rights reserved. The DuPont Oval Logo, DuPont[™], The miracles of science[™], and all products denoted with © or [™] are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its atilitates. Printed on : November 5, 2018

PRODUCT INFORMATION							
ATTRIBUTES	IBUTES DuPont™ Tychem® 2 Adhesive Closure. Box			000 Coverall. Collar. Elastic Wrists and Ankles. Storm Flap with and Seams. Yellow.			
CATALOG NUMBER QC125BYLxx0012yy (xx=size;yy=option code) When ordering, replace xx with desired size.							
FABRIC	DESIGN	SEAM	COLOR	CASE COUNT	SIZES	OPTION CODES	
Tychem® E 2000 E	Coverall w/ Elastic Wrists and Ankles	Bound	Yellow	12 per case	MD, LG, XL, 2X, 3X, 4X, 5X, 6X	00	
TYPICAL FINISHED DIMENSIONS							
OPTION CODE DESCRIPT		SCRIPTION	I SIZES		PART NUMBER		
00		Standard	MD, LG, XL, 2X, 3X, 4X, 5X, 6X		QC125BYLxx001200		
PHYSICAL PROPERTIES - F			ABRIC DATA		Typical values, not specifications.		
PROPERTY			TEST METHOD		RESULT		
Thickness			ASTM D1777		10 mils		
Basis Weight			ASTM D3776		2.5 oz/yd ²		
Burst Strength - Mullen			ASTIVI D3//6)	2.5 oz/yd		
Burst Stree	0		ASTM D3776		2.5 oz/yd 72 psi		
Tear Resista	0	r		3			
Tear Resista (I Tear Resista	ngth - Mullen nce - Trap Tea		ASTM D3786	3	72 psi		
Tear Resista (! Tear Resista (!	ngth - Mullen nce - Trap Tea MD) nce - Trap Tea	r	ASTM D3786 ASTM D1117	- 	72 psi 6.4 lb _f		
Tear Resista (f Tear Resista (f Breaking Stree	ngth - Mullen nce - Trap Tea MD) nce - Trap Tea CD)	r D)	ASTM D3786 ASTM D1117 ASTM D1117	- 	72 psi 6.4 lb _f 4.7 lb _f		