PROBRANDS

SAFETY DATA SHEET

1. Identification

Product identifier Dykem® Remover & Prep (Bulk)

Other means of identification

 Part Number
 82638, 82738, 82838, 82938

 Synonyms
 FORMULA CODE(S): * 8947

Recommended use Remover and cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 70
Ethanol		64-17-5	30 - 40
Isopropanol		67-63-0	1 - 5
N-Propyl acetate		109-60-4	1 - 5

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
N-Propyl acetate (CAS 109-60-4)	PEL	840 mg/m3	
		200 ppm	
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
N-Propyl acetate (CAS 109-60-4)	STEL	150 ppm	
	TWA	100 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
N-Propyl acetate (CAS 109-60-4)	STEL	1050 mg/m3	
		250 ppm	

Components Type Value

200 ppm

Biological limit values

ACGIH Biological	Exposure	Indices
------------------	----------	---------

	Components	Value	Determinant	Specimen	Sampling Time
	Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
	Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
* For compling details, places ago the course decument					

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release,

exposure levels are not known, or any other circumstances where air-purifying respirators may not

provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Liquid. **Form** Color Clear. Odor Solvent. **Odor threshold** Not available. Not available. Not available. Melting point/freezing point 132.98 °F (56.1 °C) Initial boiling point and boiling range

Flash point -4.0 °F (-20.0 °C) Tag Closed Cup

Evaporation rate > 1 (BuAc = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

1.7 %

Flammability limit - upper

(%)

21.2 %

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density > 1 (air = 1)

Relative density 0.79 @ 21.1°C

Material name: Dykem® Remover & Prep (Bulk)

SDS US

Solubility(ies)

Solubility (water) Completely soluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Water thin

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

VOC 36.23 %; 287 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

rossibility of nazardous

Conditions to avoid

reactions

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Ethanol (CAS 64-17-5)		
<u>Acute</u>		
Inhalation		
Vapor		
LC50	Rat	51 mg/l, 6 Hours
Isopropanol (CAS 67-63-0)		
<u>Acute</u>		
Oral		
LD50	Rat	4.7 g/kg

Components Species Test Results

N-Propyl acetate (CAS 109-60-4)

Acute Dermal

LD50 Rabbit > 18000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat 32 mg/l, 4 Hours

Oral

LD50 Rat 8700 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Acetone (CAS 67-64-1)

A4 Not classifiable as a human carcinogen.

Isopropanol (CAS 67-63-0)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Acetone (CAS 67-64-	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Ethanol (CAS 64-17-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Isopropanol (CAS 67-	63-0)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

Test Results Components **Species**

N-Propyl acetate (CAS 109-60-4)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 56 - 64 mg/l, 96 hours

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24-0.31Ethanol Isopropanol 0.05 N-Propyl acetate 1.23

Mobility in soil Not established.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1263 **UN** number

UN proper shipping name

Transport hazard class(es)

Paint related material including paint thinning, drying, removing, or reducing compound

Class 3 Subsidiary risk 3 Label(s) Ш Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 149, B52, IB2, T4, TP1, TP8, TP28

150 Packaging exceptions 173 Packaging non bulk 242 Packaging bulk

IATA

UN1263 UN number

UN proper shipping name Transport hazard class(es)

Paint related material (including paint thinning or reducing compounds)

3 **Class** Subsidiary risk Ш Packing group

Environmental hazards No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN1263 **UN** number

UN proper shipping name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) Transport hazard class(es)

Class 3 Subsidiary risk П Packing group

Environmental hazards

Marine pollutant No. F-E, S-E

EmS Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation categories

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Material name: Dykem® Remover & Prep (Bulk)

82638, 82738, 82838, 82938 Version #: 03 Revision date: 10-01-2020 Issue date: 02-26-2018

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1)

Ethanol (CAS 64-17-5)

Isopropanol (CAS 67-63-0)

N-Propyl acetate (CAS 109-60-4)

Low priority

Low priority

Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Ethanol (CAS 64-17-5) Isopropanol (CAS 67-63-0) N-Propyl acetate (CAS 109-60-4)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1) Isopropanol (CAS 67-63-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 02-26-2018

 Revision date
 10-01-2020

Version # 03

Material name: Dykem® Remover & Prep (Bulk)

SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Physical & Chemical Properties: Multiple Properties