



21033055G

(shown with mounting bracket included)

▶ Evacuator® Plus | Back-up Alarms

FEATURES

- “Plus” models offer dual-tone function (pulse or constant).
- A wide range of decibel levels and operating voltages are offered for enhanced application flexibility.
- Universal mounting bracket included.
- Maximum current draw of .015 A.
- Unique Piezo-electric design incorporates a tear-free Mylar speaker cone that is impervious to moisture.
- Solid-state electronics and a sealed design protect against moisture, contaminants and vibration.
- Three-year product warranty.

APPROVALS

- SAE J994
- OSHA
- MSHA

Built for Versatility and Durability

Federal Signal's Evacuator Plus (dual tone) back-up alarms are engineered to provide dependable performance and exceptional warning power across a diverse range of vehicle and material handling equipment requirements. Built to withstand the most punishing applications, these alarms feature piezo-electric circuitry and solid-state components that reduce Amp draw (as low as 0.02 A @ 12 VDC), and minimize the adverse effects of shock and vibration.

Multiple Options to Fit Your Needs

Evacuator Plus is the right back-up alarm for applications where two tones are better than one. The dual-function feature supplies Evacuator Plus with the ability to produce two distinctively different tones.

Dual-function Evacuator Plus models can be ordered for applications ranging from 87 dB to 112 dB thereby providing users with the flexibility to meet their most precise warning requirements.

HOW TO ORDER

Specify model

Evacuator Plus, Dual Functions, 12-48VDC

210330SSG	87 dB(A), 12-48 VDC, SAE J994 Type D, nickel-plated threaded terminals
210331SSG	97 dB(A), 12-48 VDC, SAE J994 Type C, nickel-plated threaded terminals
210333SSG	107 dB(A), 12-48 VDC, SAE J994 Type B, nickel-plated threaded terminals
210335SSG	112 db (A), 12-48 VDC, SAE J994 Type B, nickel-plated threaded terminals

SPECIFICATIONS

	210330SSG	210331SSG	210333SSG	210335SSG
Specifications				
Amp Draw	0.02 A @ 12 VDC	0.03 A @ 12 VDC	0.17 A @ 12 VDC	.17 A @ 12 VDC
Voltage	12-48 VDC	12-48 VDC	12-48 VDC	12-48 VDC
Sound Level	87 dB	97 dB	107 dB	112 db
Sound Frequency	2.75 kHz	2.4 kHz	2.7 kHz	2.7 kHz
Physical Specifications				
Length	2.9 in (7.4 cm)			
Width	2.9 in (7.4 cm)			
Height	2.4 in (6.1 cm)			
Ship Weight				
	0.6 lbs (0.3 kg)			



Evacuator is a trademark of Federal Signal Corporation.

©2019 Federal Signal Corporation. M9011 | 519