



model SP11FC

Eyewash Head

FEATURES & BENEFITS

OPTIONS

For more information, visit www.hawesco.com or call (888) 640-4297.




SPECIFICATIONS

Model SP11FC is a Soft-Flo ABS plastic anti-surge eyewash head in Safety Green, with a built-in 1.2 gpm (4.5 L) automatic pressure compensation flow control. This assures a single, soft-and-steady stream of water for flowing water pressure ranging from 30 to 90 psi (2.1 to 6.2 bar). Flow control is easily accessible for cleaning. Supply: 1/4" NPT.

APPLICATIONS

NOTES

1. MODEL SP11FC IS DESIGNED FOR 1.2 GPM FLOW.
2. ASSEMBLY INSTRUCTIONS:
 - STEP 1. REMOVE OLD EYEWASH HEAD.
 - STEP 2. MAKE SURE THREADS ARE CLEAN.
 - STEP 3. SCREW ON NEW EYEWASH HEAD UNTIL HAND TIGHT. DO NOT USE PIPE SEALANT AS THIS COULD DAMAGE EYEWASH HEAD. TEFLON TAPE CAN BE USED BUT NOT REQUIRED.
 - STEP 4. TURN ON VALVE & CHECK FLOW PATTERN USING EYEWASH GAGE PER ANSI Z358.1.



		INFO FAX : 1-888-FAX-HAWS (1-888-329-4297) 1455 Kleppe Ln Sparks NV, 89431 Phone: 775-359-4112 Fax: 775-359-7424 Haws Ag Building 3 CH-3401 Burgdorf Switzerland Haws Wng Pte Ltd 74 Sungai Kodut Loop Singapore 729531 e-mail: Haws@hawsco.com Website: www.hawsco.com	
ORDER PART NO. ECN: 2880 R: MIKULSKI APPROVED:	TITLE: EYEWASH HEAD, SP11FC MODEL: SP11FC INFO FAX DOC #: 27271132	DATE: 10/00 DRAWN: RTM SCALE: 1/2 DRAWING TYPE:	PART NUMBER: 14845A00 REV: 0 SIZE: A SH: 1 OF 1