

SPC105 features blue coverstock on one side.

SPC® Oil Absorbents

- Brady SPC's best-selling oil only pads for industrial or marine use
- Floats indefinitely even when saturated with oil
- Efficient single-ply construction of MAXX® Technology absorption and strength without the extra weight
- Packaged in a blue bag to streamline absorbent identification in your facility

Features:

- For Oils, Coolants, Solvents and Oil-based Fluids
- No Coverstock (1-Ply)
- Medium Durability
- Medium Linting

- Perforated & Dimpled
- Floats Indefinitely
- Heavy, Medium & Light Weights

Recommended For:

- Anywhere there is a leak, drip or spill
- · Marine and environmental spills
- · Oil refineries / fuel chemical
- General manufacturing

| Catalog # | Туре | Size | Perforated | Absorbency Factor (gl/gs) | Absorbency Capacity (gal) | Shipping Wt (lbs) | Pallet Qty. | Quantity |
|-----------|---|----------|------------|------------------------------|------------------------------|----------------------|----------------|-----------|
| Pads | | | | | | | | |
| SPC50 | Heavy Wt. Pad | 33"x39" | No | 18 | 73 | 33.5 | 10 | 50/bale* |
| SPC100 | Heavy Wt. Pad | 15"x19" | Yes, 7.5" | 18 | 35 | 14 | 30 | 100/bale* |
| SPC105 | Heavy Wt. Pad (1 side w/blue coverstock) | 15"×19" | Yes, 7.5" | 18 | 24 | 14 | 30 | 100/bale* |
| SPC300 | Medium Wt. Pad | 15"x19" | Yes, 7.5" | 18 | 30 | 11 | 30 | 100/bale* |
| SPC200 | Light Wt. Pad | 15"x19" | Yes, 7.5" | 18 | 40 | 16 | 24 | 200/bale* |
| SPC500 | Light Wt. Pad | 15"x19" | Yes, 7.5" | 18 | 20 | 8.2 | 36 | 100/bale* |
| Rolls | | | | | | | | |
| SPC150 | Heavy Wt. Roll | 38"x144' | No | 15 | 70 | 33 | 18 | 1/bale* |
| SPC152 | Heavy Wt. Roll | 19"x144' | No | 15 | 70 | 33 | 18 | 2/bale* |

^{*}SPC Oil Absorbents packaged in a blue bag.



BASIC Oil Absorbents

- · Value-priced oil only absorbent
- Floats indefinitely even when saturated with oil
- Packaged in a clear bag to streamline absorbent identification in your facility
- Economical single-ply pads & rolls made of oil only meltblown polypropylene

Features:

- For Oils, Coolants, Solvents and Oil-based Fluids
- No Coverstock (1-Ply)
- Light Durability
- High Linting

- · Perforated & Dimpled
- Floats IndefinitelyHeavy & Light Weights
- · Cost: \$

Recommended For:

- · Anywhere there is a leak, drip or spill
- General industrial or manufacturing oil only applications
- · Marine and environmental spills
- · Coast guard or on-board vessels

| Catalog # | Туре | Size | Perforated | Absorbency Factor (gl/gs) | Absorbency Capacity (gal) | Shipping Wt (lbs) | Pallet Qty. | Quantity |
|-----------|----------------------|----------|----------------|------------------------------|------------------------------|----------------------|----------------|----------|
| Pads | | | | | | | | |
| BPO100 | Heavy Wt. Pad | 15"x17" | Yes, 7.5" | 18 | 20.5 | 8.5 | 30 | 100/bale |
| BPO200 | Light Wt. Pad | 15"x17" | Yes, 7.5" | 18 | 34 | 14 | 24 | 200/bale |
| BPO500 | Light Wt. Pad | 15"x17" | Yes, 7.5" | 18 | 17 | 7 | 36 | 100/bale |
| Rolls | | | | | | | | |
| BRO150 | Heavy Wt. Roll | 30"x150" | Yes, every 30" | 14.5 | 38 | 19.5 | 18 | 1/bale |
| BRO152 | Heavy Wt. Split Roll | 15"x150" | Yes, every 30" | 14.5 | 38 | 19.5 | 18 | 2/bale |