# CRO

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Equa-Torque® Differential Friction Modifier

Other means of identification

Product code No. SL2411 (Item# 1007797)

Recommended use Differential friction modifier

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

**Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

**Hazard statement** Harmful to aquatic life with long lasting effects.

Precautionary statement

**Prevention** Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying. Avoid release to the environment.

Category 3

**Response** Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	60 - 70
alkylamine salt of alkyl phosphoric acid		Proprietary	30 - 40
methanol		67-56-1	< 0.2

Material name: Equa-Torque® Differential Friction Modifier

No. SL2411 (Item# 1007797) Version #: 02 Revision date: 08-22-2017 Issue date: 05-21-2015

4	First	-aid	mea	sures
<b>T</b> .	IIIJL	-aiu	IIICa	Jui CJ

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Inhalation

Call a physician if symptoms develop or persist.

Rinse skin with water/shower. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately. Ingestion Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and special treatment needed

Treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

General fire hazards

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

# 7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.	
methanol (CAS 67-56-1)	PEL	2000 mg/m3 500 ppm 260 mg/m3		

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
		200 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
methanol (CAS 67-56-1)	STEL	325 mg/m3 250 ppm	
	TWA	260 mg/m3 200 ppm	

#### **Biological limit values**

ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

methanol (CAS 67-56-1) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

methanol (CAS 67-56-1) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

methanol (CAS 67-56-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

Hand protectionOtherWear protective gloves such as: Nitrile.Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

Material name: Equa-Torque® Differential Friction Modifier

1 2015

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. Liquid. **Form** Amber. Color

Odor Mild petroleum. Odor threshold Not available. Not available.

55.4 °F (13 °C) estimated Melting point/freezing point Initial boiling point and boiling 680 °F (360 °C) estimated

range

309.2 °F (154 °C) Pensky-Martens Closed Cup Flash point

36 % estimated

**Evaporation rate** Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower 7.3 % estimated

(%)

Flammability limit - upper (%)

3.9 hPa estimated Vapor pressure Not available. Vapor density 0.9 - 0.93Relative density Solubility (water) Insoluble. Not available. **Partition coefficient** 

(n-octanol/water)

500 °F (260 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. 35 mm<sup>2</sup>/s Viscosity (kinematic) Viscosity temperature 104 °F (40 °C) Percent volatile 60.1 % estimated

Other information

Pour point 5 °F (-15 °C)

#### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Carbon oxides. Oxides of phosphorus. Phosphorus compounds. Hazardous decomposition

products

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Prolonged skin contact may cause temporary irritation. Skin contact Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Health injuries are not known or expected under normal use.

No. SL2411 (Item# 1007797) Version #: 02 Revision date: 08-22-2017 Issue date: 05-21-2015

Material name: Equa-Torque® Differential Friction Modifier

Direct contact with eyes may cause temporary irritation.

#### Information on toxicological effects

Acute toxicity

Components **Species Test Results** 

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

**Acute** 

Dermal

> 2000 mg/kg LD50 Rabbit

Oral

**LD50** Rat > 5000 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

### 12. Ecological information

methanol (CAS 67-56-1) **Aquatic** 

Crustacea

Harmful to aquatic life with long lasting effects. **Ecotoxicity** 

rionity		riammar to aquatio me mar tong taoming emotion		
Components		Species	Test Results	
alkylamine salt of alky	l phosphoric acid			
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	91 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours	
distillates (petroleum)	, hydrotreated heav	y naphthenic (CAS 64742-52-5)		
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	1000 mg/l, 48 hours	
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours	

Material name: Equa-Torque® Differential Friction Modifier

EC50

SDS US 5/8 No. SL2411 (Item# 1007797) Version #: 02 Revision date: 08-22-2017 Issue date: 05-21-2015

Water flea (Daphnia magna)

> 10000 mg/l, 48 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Components **Species Test Results** 

LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours Fish

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methanol -0.77

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Not regulated. Hazardous waste code

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

#### 14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

#### 15. Regulatory information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**CERCLA Hazardous Substances: Reportable quantity** 

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Administration (FDA) Not regulated.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

**Section 311/312** Immediate Hazard - No Delayed Hazard - No **Hazard categories** Fire Hazard - No

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

#### **US** state regulations

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) methanol (CAS 67-56-1)

#### US. New Jersey Worker and Community Right-to-Know Act

methanol (CAS 67-56-1)

#### **US. Massachusetts RTK - Substance List**

methanol (CAS 67-56-1)

#### US. Pennsylvania Worker and Community Right-to-Know Law

methanol (CAS 67-56-1)

#### **US. Rhode Island RTK**

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) methanol (CAS 67-56-1)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

methanol (CAS 67-56-1) Listed: March 16, 2012

# US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

cyanide (CAS 57-12-5) Listed: July 5, 2013

#### Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR Not determined

51.100(s))

**Consumer products** Not regulated

(40 CFR 59, Subpt. C)

State

Not regulated **Consumer products** VOC content (CA) < 65 % VOC content (OTC) < 65 %

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date05-21-2015Revision date08-22-2017Prepared byAllison Yoon

Version # 02

Further information CRC # 753/1002769

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

**NFPA** ratings



**Disclaimer** The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

**Revision Information**This document has undergone significant changes and should be reviewed in its entirety.