

PRODUCT SPECIFICATION

CATALOG NUMBER: See table below

DESCRIPTION: 6/3 & 8/1 SEOW, 125/250V 50A outdoor use cord set with

"California Standard" twist-to-lock plug and cord connector


CONSTRUCTION PARAMETERS:

Conductors: (3) 6 AWG, 96/26 bunched bare copper

(1) 8 AWG, 96/28 bunched bare copper

Jacket material: TPE, black

Overall cable O.D. (nom): 0.868"



CS6364C CS6365C

Plug and connector manufacturer: Hubbell Wiring Device

Plug and connector configuration: 50A 125/250V 3 pole 4 wire grounding,

non-NEMA "California Standard"

Plug and connector materials: Thermoplastic polyester interior with nylon cover

Neoprene cord gasket Stainless steel plug shroud

PROPERTIES:

Temperature rating of cable: -40 to +90 deg C

Electrical ratings: 125/250 VAC, 50A

Catalog number	Length	Case qty	UPC
19380008	50 ft	1	0 29892 01938 9
19390008	100 ft	1	0 29892 01939 6

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company, LLC.