JAT-621, 1/2" REVERSIBLE AIR DRILL

505621

Rated to last for those demanding 12 hour days, the R12 Series air tools are built to tackle the most extreme jobs. Engineered for Overtime, these tools feature the superior strength and durability needed across a wide range of applications.



FEATURES

- · Impact resistant composite housing reduces tool weight, improving balance and reduces user fatigue.
- Sealed Ball bearing design keeps out contaminants promoting smooth operation
- Side-mounted, forward/reverse switch for quick and easy direction changes
- Industrial Jacobs's keyed chuck efficiently transfers torque when needed
- Rugged, ball-bearing design for durability
- Auxiliary side handle for increased control
- Variable-speed trigger for precise speed control
- Performace @ 90 PSI. Air Inlet NPT 3/8". Min Hose Size 3/8"



RED ASSURANCE LIFETIME WARRANTY

We are confident of every Air Tool we manufacture. To prove it, we back every Air Tool that bears the JET name with a Lifetime Warranty. The JET Lifetime Warranty covers manufacturer's defects, but does not cover misuse, abuse, accidents, negligence, wear and tear, improper repair or alternations.



1 YEAR 'WEAR & TEAR' COVERAGE

JET covers all Air Tool repair costs including parts and labor for the first year of ownership. Proof of purchase is required. JET's 'Wear & Tear' Coverage does not cover misuse, abuse, accidents, negligence, improper maintenance, repair or alterations.

STAND BEHIND YOUR WORK™



JAT-621, 1/2" REVERSIBLE AIR DRILL

505621

SPECIFICATIONS

Classification	R 12
Spindle Thread (In./TPI)	3/8"-24
Chuck Size (In.)	1/2
Free Speed (RPM)	800
Horse Power (HP)	0.5
Air Inlet (NPT/In.)	1/4
Air Hose (ID/In.)	3/8
Air Pressure (PSI)	90
Air Consumption (CFM)	4
Sound Pressure (db) (A)	83
Sound Power (db) (A)	90
Vibration Value (m/s²)	0.4
Overall Length (In.)	8-5/8
Weight (Lbs.)	3.46





JAT-621, 1/2" REVERSIBLE AIR DRILL

505621

FULL SERIES

STOCK NO	MODEL NO	CLASSIFICATION	SPINDLE THREAD (IN./TPI)	CHUCK SIZE (IN.)	FREE SPEED (RPM)	HORSE POWER (HP)
505621	JAT-621	R 12	3/8"-24	1/2	800	0.5
505620	JAT-620	R 12	3/8"-24	3/8	1,800	0.5
505630	JAT-630	R 12	3/8"-24	3/8	1,200	0.5

