



PROTECTIVE INDUSTRIAL PRODUCTS

280-EV6151 Specification Sheet

EVOLUTION™ DELUXE 6151 - TYPE I HARD HAT

PRODUCT DESCRIPTION:

- HDPE shell designed with five raised channels running across the top of the helmet for strength.
- 6-Point Suspension System.
- Wide polyester textile webbing harness.
- Unique “3D Adjustment” provides a precise helmet fit using harness depth settings.
- Evolution Wheel Ratchet is easy to use and creates a firm comfortable fit.
- Vented version available to reduce inside helmet temperatures (ANSI Class C).
- Short brim version available for improved vision when looking up.
- Chamlon™ Sweatband.
- Universal slots to fit various accessories.
- Packed ready-to-wear with no assembly required.

Applications:

Provide protection from falling debris, low hanging objects and electrical hazards. The use of ANSI compliant head protection is required by OSHA and helps workers avoid serious injury.

CONFORMITY:

Meets and exceeds ANSI/ISEA Z89.1-2009, Type I Class E standards.
Meets ANSI requirements for Reverse Donning and Lower Temperature (LT).
Vented hard hat versions have a Class C (Conductive) electrical rating.

TECHNICAL DATA:

Suspension: 6-point

Adjustment: Revolution™ wheel ratchet

Brim: Standard or Short

Shell: Non-vented or Vented

Material:

Shell: High Density Polyethylene (HDPE)

Suspension: HDPE headband & webbing clips with 1” wide polyester textile webbing straps

Brow Pad: Chamlon™ Egyptian cotton core with porous PU coating, PH neutral, dermatologically tested

Available Sizes: One size fits all

Country of Origin/Harmonization Code: UAE/6506.10.6075

PACKAGING:

Packaging: 1 per polybag; 10 per case

Case Dimensions: (cm) - 58.4 x 24.1 x 45.5 / (in) - 23 x 9.5 x 18

Case Weight: 3.8 kg / 8.375 lbs



HELMET SIZING & WEIGHT:

Sizing is adjustable via the wheel ratchet

Hat Size	6 5/8 - 8
(cm)	53 - 64
(in)	20 7/8 - 25
Weight	13.2 ounces / 374 grams

INSTRUCTIONS FOR USE:

Fit hard hat on head and ensure the hard hat is adjusted to the size of the user's head. Fasten chin strap (if available) to ensure fit. The harness depth can also be adjusted on this helmet using the unique “3D Adjustment” setting for a precise fit.

LIMITATIONS OF USE:

- Protection will only be offered if the hard hat is fitted correctly.
- Any hard hat subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer.
- The suspension, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice.
- The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer.

This document is the property of PIP and the information contained herein is proprietary to PIP.

Protective Industrial Products | 26 Computer Drive East | Albany, NY 12205

Phone: 518-861-0133 | Toll free: 800-262-5755 | Fax: 518-861-0144 | www.pipusa.com | sales@pipusa.com



PROTECTIVE INDUSTRIAL PRODUCTS

280-EV6151 Specification Sheet

EVOLUTION™ DELUXE 6151 - TYPE I HARD HAT

CLEANING & MAINTENANCE:

The shell may be cleaned with soap and warm water and dried with a soft cloth. The hard hat should not be cleaned with chemical or abrasive cleaners. The hard hat should be stored out of direct sunlight, and away from chemicals and extremes of temperature.

CUSTOM IMPRINTING:

Available on the Front, Rear and Sides of this helmet; up to 4-color printing. MOQ is 40 helmets.

BARCODE #	COLOR	BRIM	SHELL	UPC EACH	UPC CASE
280-EV6151-10	White	Standard	Non-vented	5038428136716	5038428811934
280-EV6151-20	Yellow	Standard	Non-vented	5038428136723	5038428811941
280-EV6151-30	Green	Standard	Non-vented	5038428136730	5038428811958
280-EV6151-50	Blue	Standard	Non-vented	5038428136747	5038428811965
280-EV6151-60	Red	Standard	Non-vented	5038428136754	5038428811972
280-EV6151-80	Orange	Standard	Non-vented	5038428136761	5038428811989
280-EV6151-LY	Bright Lime Yellow	Standard	Non-vented	5038428136785	5038428812009
280-EV6151-OR	Bright Orange	Standard	Non-vented	5038428136778	5038428811996
280-EV6151V-10	White	Standard	Vented (Class C)	5038428136815	5038428812030
280-EV6151V-20	Yellow	Standard	Vented (Class C)	5038428136822	5038428812047
280-EV6151S-10	White	Short	Non-vented	5038428136853	5038428812078
280-EV6151S-20	Yellow	Short	Non-vented	5038428136860	5038428812085
280-EV6151SV-10	White	Short	Vented (Class C)	5038428136877	5038428812092
280-EV6151SV-20	Yellow	Short	Vented (Class C)	5038428136884	5038428812108



10
White



20
Yellow



30
Green



50
Blue



60
Red



80
Orange



LY
Bright Lime
Yellow



OR
Bright Orange

This document is the property of PIP and the information contained herein is proprietary to PIP.