

Revision Number: 001.2 Issue date: 12/15/2015

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8034 SYN. GREASE HIGH IDH number: 457458

PERFORM. known as ViperLube(TM)

**Synthetic Grease** 

 Product type:
 Lubricant
 Item number:
 36783

 Restriction of Use:
 None identified
 Region:
 United States

Company address: Contact information:

Henkel Corporation Telephone: (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
WARNING:	CAUSES SERIOUS EYE IRRITATION.		
	CAUSES SKIN IRRITATION.		

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

**Prevention:** Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves. **Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison control center or physician. If skin irritation occurs: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

# See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
White mineral oil (petroleum), highly refined	8042-47-5	60 - 100

IDH number: 457458 Product name: LOCTITE LB 8034 SYN. GREASE HIGH PERFORM. known as ViperLube(TM)
Synthetic Grease

Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	148520-84-7	10 - 30
Diboron calcium tetraoxide	13701-64-9	1 - 5
Calcium dodecylbenzene sulfonate	26264-06-2	1 - 5

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

Inhalation: No specific treatment is necessary since material is not likely to be hazardous

by inhalation. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Seek medical attention from a specialist.

**Ingestion:** Do not induce vomiting. Consult a physician if necessary.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: None
Unusual fire or explosion hazards: None

IDH number: 457458

**Hazardous combustion products:** Oxides of carbon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Scrape up as much material as possible. Store in a partly filled, closed

container until disposal.

# 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Do not wear contact lenses.

Storage: For safe storage, store between 8 °C (46.4 °F) and 28 °C (82.4 °F)

Store in a dry area below 90° F.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
White mineral oil (petroleum), highly refined	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 5 mg/m3 PEL Mist.	None	None
Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	None	None	None	None
Diboron calcium tetraoxide	6 mg/m3 STEL Inhalable fraction. 2 mg/m3 TWA Inhalable fraction.	None	None	None
Calcium dodecylbenzene sulfonate	None	None	None	None

Engineering controls: General room ventilation is usually adequate. Use local exhaust ventilation if

the potential for airborne exposure exists.

Respiratory protection: No personal respiratory protective equipment normally required. Breathing

apparatus only if aerosol or dust is formed.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Chemical resistant, impermeable gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Tan Odor: Mild

Odor threshold:

pH:

Vapor pressure:

Boiling point/range:

Mot available.

Not available.

Not available.

> 260 °C (> 500°F)

Melting point/ range:

Not available.

Specific gravity: 0.96

Vapor density:

Not available.

Flash point:

Product is a solid.

Flammable/Explosive limits - lower: Not applicable Not applicable Flammable/Explosive limits - upper: Not applicable Not applicable

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not available.

**VOC content:** < 1 %; < 10 g/l Estimated

Viscosity:Not available.Decomposition temperature:Not available.

IDH number: 457458

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 457458

Oxides of carbon. Formaldehyde.

**Incompatible materials:** Acids and bases. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Excessive heat.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Eye contact

#### **Potential Health Effects/Symptoms**

Inhalation: This product has low volatility and is not expected to cause respiratory tract irritation during

normal conditions of use. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations

below the OSHA permissible limit.

Skin contact: May cause skin irritation.

Eye contact: May cause irritation.

**Ingestion:** Not expected to be harmful by ingestion.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
White mineral oil (petroleum), highly refined	None	Irritant
Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	None	No Records
Diboron calcium tetraoxide	None	No Records
Calcium dodecylbenzene sulfonate	None	Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
White mineral oil (petroleum), highly refined	No	No	No
Benzene, mono-C10-13-alkyl derivs., fractionation bottoms, heavy ends, sulfonated, calcium salts	No	No	No
Diboron calcium tetraoxide	No	No	No
Calcium dodecylbenzene sulfonate	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: No specific studies have been conducted by Henkel on the ecotoxicity or

environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components

to the atmosphere are not believed to entail significant ecological

consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up

immediately in accordance with Section 6.

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
None
Packing group:
None

International Air Transportation (ICAO/IATA)

**Proper shipping name:** Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9

Identification number:UN 3082Packing group:III

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

IDH number: 457458 Product name: LOCTITE LB 8034 SYN. GREASE HIGH PERFORM. known as ViperLube(TM)

Synthetic Grease

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

**Issue date:** 12/15/2015

IDH number: 457458

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.