BLOW GUNS

COMPACT BLOW GUN W/RUBBER TIP

- · Includes One Rubber Tip and One Safety Tip
- · Zinc Alloy Body
- 1/4" FPT Inlet
- · Maximum 150 psi (Recommended Working
- Pressure 90-120 psi) · Safety Tip Limits Air Pressure to 30 psi When Dead-Ended
- per OSHA requirement
- Maximum 87 dba
- 1/8" Outlet



| Part # | Size | List Price |
|---------|------|------------|
| 320-053 | 1/4" | 9.66 |

SAFETY BLOW GUN

- · Heavy-Duty Design
- · Internal Safety Valve that Limits Air Pressure to Less than 30 psi When dead-ended per OSHA
- · Aluminium Alloy Body
- 1/4" FPT Inlet
- · Maximum 150 psi (Recommended Working Pressure 90-120 psi)
- · Safety Tip Limits Air Pressure to 30 psi When Dead-Ended per OSHA Requirement
- Maximum 87 dba
- 1/8" Outlet



| Part # | Size | List Price |
|---------|------|------------|
| 320-054 | 1/4" | 9.38 |

SAFETY BLOW GUN

- N/P steel handle with plastic sleeve
- Brass Valve
- Zinc body Aluminum nozzle



| 1/ | 8" | Οu | ıtlet |
|----|----|----|-------|
|----|----|----|-------|

| Part # | Part # Size | | Size | e List F | | 'rice | |
|--------------|-------------|-----|-----------|----------|---------|-------|--|
| 320-05 | 50 | 1 | /4" Inlet | | 9.29 | | |
| 511 <i>1</i> | E1 124 | 401 | 20420VD | C1/10 | D204 20 | 6175 | |

COMPACT BLOW GUN

- · With standard tip and safety tip
- Zinc Alloy Body
- 1/4" FPT Inlet
- Maximum 150 psi (Recommended Working Pressure 90-120 psi)
- · Safety Tip Limits Air Pressure to 30 psi When Dead-Ended per OSHA Requirement
- Maximum 87 dba



PNEUMATIC ACCESSORIES

PISTOL GRIP BLOW GUN

- · Lightweight, Ergonomic Design
- Delrin® Body
- Trigger Air Flow Control
- 1/4" FPT Inlet
- 3" Nozzle Ideal for Tight Spaces
- Recommended Working Pressure 90-120 psi
- Maximum 87 Dba

| | | • |
|---------|------|------------|
| Part # | Size | List Price |
| 320-036 | 1/4" | 7.84 |

PISTOL GRIP BLO-GUN

150 PSI

Material

- Body: POM (engineering plastic)
- · Nozzle: nickel plated carbon steel
- Blue Handle Color

Features

- Simple construction, economic
- · Global thread connection
- · Durable and versatile applications
- 4 inch nozzle

| Part # | Size | List Price |
|---------|------|------------|
| 320-035 | 1/4" | 8.92 |

RUBBER TIPPED NOZZLE



Makes positive seal between gun and fuel line or other openings. Use only on air line regulated to 30 PSI or less

| Part # | Thread Size | List Price |
|---------|-------------|------------|
| 320-070 | 1/8 - 27 | 7.83 |

51-521 2058 D201RT 411R

HIGH FLOW SAFETY NOZZLE



Meets OSHA regulations of 30 PSI maximum outlet pressure when line pressure is 150 PSI or less. Has an air pressure bypass which prevents build up of tip pressure even if nozzle is blocked. Adapts to any blow gun with a 1/8" NPT nozzle port

| Part # | Size | List Price |
|---------|------------------|------------|
| 320-075 | 1/8 MIP x Female | 2.98 |

51-338 SST10 411BT 2056