

Dependable protection with a reliable grip

- Prevents rips and tears due to thicker fingertips than most standard latex gloves
- Delivers a secure and dependable grip for rugged work settings especially in oily environments
- Allows easy donning and a cooler, drier and more comfortable fit
- Provides excellent protection for automotive industry applications



Industries

- Automotive
- Dental
- Electronics
- General Exam
- Healthcare
- Laboratory
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices)

Applications

- Analytical testing/measurements
- Assembly and inspection of oil-coated pieces
- Cleaning
- Crime scene evaluation
- Dental
- Filtration Processes
- Food and dairy processing
- Handling small parts
- Healthcare
- Janitorial and maintenance work
- Paint and spray shops
- Picking and assembling wet or dry parts
- Protection from blood and other bodily fluids
- Re-fueling
- Warehousing

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

| | |
|---|--|
| | Diamond Grip[™] |
| Material | Latex |
| Color | Natural |
| Glove Design | Ambidextrous, Powder-Free, Double Chlorinated, Textured Fingertips |
| Cuff | Beaded Cuff |
| Manufacturing/ QMS Audit Standards | ISO 13485 |
| Regulatory/Standards Compliance | ASTM D3578, US QSR/FDA 510(K) MEDICAL (EXAMINATION) GRADE, COMPLIANT WITH U.S. FOOD CONTACT REGULATIONS |
| Packaging | 100 Pack: 100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton. 10 Pack: 10 gloves per pouch, 50 pouches per shipping carton, 500 gloves per shipping carton. |
| Storage | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country of Origin | Malaysia |
| User Needs Segment | Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times. |

PHYSICAL PROPERTIES:

| | TYPICAL VALUES | | | | | TESTING METHOD |
|--|---------------------------|--------------|--------------|--------------|----------------|---------------------|
| | 5.5 - 6 XS | 6.5 - 7 S | 7.5 - 8 M | 8.5 - 9 L | 9.5 - 10 XL | |
| Length (mm/in.) | 245/9.6 | 245/9.6 | 245/9.6 | 245/9.6 | 245/9.6 | ASTM D3767/EN 420 |
| Average Palm Width (mm/in.) | 76/2.99 | 83/3.26 | 95/3.74 | 107/4.21 | 117/4.60 | |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | | | | ASTM D5151/EN 374-2 |
| Palm Thickness Single Wall | (mm : 0.16) / (mil : 6.3) | | | | | ASTM D3767/EN 420 |
| | BEFORE AGING | | AFTER AGING | | | |
| Ultimate Tensile Strength | > 27 Mpa | | > 23 Mpa | | ASTM D 412-06a | |
| Elongation at Break (%) | > 750 | | > 600 | | ASTM D 412-06a | |
| Force at break (N) | 16 | | 6 | | EN 455-2 | |

ORDERING INFORMATION:

| | SIZE | 5.5 - 6 XS | 6.5 - 7 S | 7.5 - 8 M | 8.5 - 9 L | 9.5 - 10 XL |
|---|-------------|---------------|--------------|--------------|--------------|----------------|
| Diamond Grip 100 glove dispenser | REORDER NO. | MF-300-XS | MF-300-S | MF-300-M | MF-300-L | MF-300-XL |
| Diamond Grip 10 pack pouch is only available in Large | | | | | MF-300-RP | |

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

Warning: This product contains natural rubber latex, which may cause allergic reactions in sensitive individuals.

For additional information visit us at www.ansell.com, or call us at 1-877-750-6110

Ansell
111 Wood Avenue South
Suite 210
Iselin, NJ 08830
USA

Ansell
105 Lauder
Cowansville, QC J2K 2K8
Canada