

XPP-5566RX/GX

INTRANT™ Intrinsically Safe Permissible Dual-Light™ Angle Light

MARKET APPLICATIONS

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

DESCRIPTION

This Dual-Light™ Angle Light is a Flashlight, a Floodlight and a Dual-Light Angle Light that is cULus and NFPA certified Intrinsically Safe Permissible. The flashlight setting offers 3 user-selectable brightness settings of 200, 110 and 60 Lumens plus a strobe feature with a 420 meter beam distance. The floodlight setting has 3 user-selectable brightness settings as well and a Survival Mode of 20 lumens that provides just enough light in an emergency situation with a runtime of 33 hrs. Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them. It's powered by 3 included AA batteries and can be upgraded to a rechargeable model. Meets requirements of NFPA-1971-8.6 (2013).

CASE MATERIAL

Glass-filled Nylon Polymer

LIGHT SOURCE

Cree® LED. Impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT

Flashlight: High-200 Lumens, Medium-110 Lumens, Low-60 Lumens • Floodlight: High-100 Lumens, Medium 40

Lumens • Survival 20 Lumen • Dual-Light-205 Lumens

RUN-TIME

Flashlight: High-11 hrs, Medium-18 hrs, Low-33 hrs • Floodlight: High-11 hrs, Medium-18 hrs • Survival-33 hrs • Dual-

Light-11 hrs

BATTERY

3 AA Batteries (included)

FEATURES

- CREE® LED technology 50,000 + hours LED life
- · Multi-angle articulating head
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the floodlight including a 20 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time)
- · Glass-filled Nylon Polymer housing
- · Dual body switches
- Heavy-duty stainless-steel pocket clip with V-ring
- Dustproof / Waterproof
- Impact and chemical resistant
- Meets requirements of NFPA-1971-8.6 (2013)
- Powered by 3 AA batteries (included)
- · Upgradeable to rechargeable
- · Limited Lifetime Warranty

WARRANTY APPROVALS Limited Lifetime Warranty







FL1 STANDARD	HIGH	MEDIUM	LOW
31/5	200 LUMENS	110 LUMENS	60 LUMENS
0	11h	18h	33h
	420m	250m	187m
	41000cd	15625cd	8750cd
2m			
1m			