

NIGHTSTICK[®]

Intrinsically Safe Permissible Dual-Light™ Cap Lamp Rechargeable



TECHNOLOGY

Spot High



Spot Low



Flood High



Survival



Dual



90 Spotlight
Lumens

90 Floodlight
Lumens

180 Dual-Light™
Lumens



- MSHA certified Intrinsically Safe Permissible
- Spotlight/Floodlight/Dual-Light™
- User-selectable brightness settings on spotlight & floodlight including 5 lumen "Survival" mode
- Powered by an integrated rechargeable Lithium-ion battery

The XPR-5560G Rechargeable Intrinsically Safe Permissible Dual-Light™ Cap Lamp features a spotlight, a floodlight and a dual-light that is MSHA certified Intrinsically Safe Permissible. The spotlight setting offers 2 user-selectable brightness settings of 90 lumens on high mode and 45 lumens on low mode. The floodlight setting offers 90 lumens on high mode along with a "Survival Mode" of 5 lumens that provides just enough light in an emergency situation with a run-time of 170 hrs. The Dual-Light mode allows the user to turn on both the spotlight and the flood light on simultaneously for maximum lighting versatility and user safety. The XPR-5560G is powered by an integrated rechargeable Lithium-ion battery.

**INTRINSICALLY SAFE
PERMISSIBLE**



XPR 5560G

Intrinsically Safe Permissible Dual-Light™ Cap Lamp Rechargeable



FEATURES

- MSHA certified Intrinsically Safe Permissible
- CREE® LED technology – 50,000+ hours LED life
- Spotlight/Floodlight/Dual-Light™
- 2 User-selectable brightness settings on the spotlight
- 2 User-selectable brightness settings on the floodlight including a 5 lumen “Survival” mode
- Dual-light (both the spotlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled nylon polymer housing with a 304 stainless steel bezel
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Waterproof
- Impact & chemical resistant
- Powered by an integrated rechargeable Lithium-ion battery
- Limited Lifetime Warranty*



Spotlight Beam For Distance Illumination

Wide-beam Floodlight For Close-up Illumination

SPECIFICATIONS

- Spotlight Lumens – High: 90, Low: 45
- Floodlight Lumens – High: 90, Survival: 5
- Dual-Light Lumens – High: 180, Low: 90
- Spotlight Run-time – High: 15hrs, Low: 22hrs
- Floodlight Run-time – High: 15hrs, Survival: 170hrs
- Dual-Light Run-time – High: 6hrs, Low: 14hrs
- Candela – High: 553, Low: 362
- Beam Distance – High: 47m, Low: 38m
- Water / Dust rating: IP-67
- Drop Rating – 2m
- Length: 2.4 in (61 mm), Width: 2.6 in (66 mm), Height: 3.5 in (89 mm)
Bezel Diameter: 2.4 in (61 mm), Weight: 6.1 oz (175 g)

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	180 LUMENS	90 LUMENS	45 LUMENS
	6h	15h	22h
	54m	47m	38m
	741cd	553cd	384cd
	2m		
	1m		

SAFETY RATING

Bayco Products, Inc.

Model XPR-5560 Permissible Cap Lamp Assembly



APPROVAL No. 19-A160003-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: Only to be charged on the surface, or underground in accordance with the applicable regulations pertaining to battery-charging stations (reference 30 CFR 75.340) with a Bayco Products, Inc. Model 5560-CHGR1. Do not open in areas where permissibility is required.

INCLUDED

- Cap Lamp
- Integrated Rechargeable Lithium-ion Battery
- Charger
- AC & DC Power Supplies



Model	UPC 0 17398
XPR-5560G	80569 8

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.