# GG504T/GC504TN

CAPSTONE® 500 SERIES





- · Fits over prescription glasses.
- · Cylinder lens is coated to prevent fogging.
- Soft PVC body conforms to facial contours for comfort fit.
- Dual purpose goggle adaptable to many different applications.
- Removble vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance.

# Bridge: 45mm Lens Base: 5.5 curve Lens Size Diagonal: 154mm Lens Size Vertical: 78mm Lens Thickness: 2.3mm Overall Length (Lens-Tip): 91mm Overall Width (Hinge-Hinge): 180mm PD: 68mm Weight: 92gm Strap Length: 540mm Closest point between temple tips: N/A, strap Closest point between temple tips: N/A, single lens Case Weight: 49.76lbs Case Pack: 144

## **GG504T/GC504TN** CAPSTONE® 500 SERIES

PACKAGING
Polybag: 1pc
Bulk in an outer carton: 144 pcs

COMPONENT	MATERIAL	FEATURES		
Lens	Polycarbonate	Single & cylinder lens		
Body	PVC	Polyvinyl chloride, flexible fit		
	Polycarbonate	Vent parts for air flow		
Nose Piece	PVC	Universal integral to frame		
Headband	Textile Elastic	Adjustable Elastic		

PART	LENS	LENS MARKING	FRAME MARKING
GG504T	Clear (Anti-Fog)	P Z87 +	Z87 + / P c SEI CAN/CSA Z94.3-07
GC504TN	Clear (Anti-Fog)	P Z87 +	Z87 +

### **LENS MARKING**

### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

### **UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

### **Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

### FRAME MARKING

### Symbols:

P: Manufacturer's mark

**Z87**: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices