

ALAIR®

Fashionable Economy Spectacle

**Part**

S3210S••

S3210ST•••

S3220S••

S3230S••

S3260S••

S3270S•

S3275S•

S3280S•

Lens and Temples
 Clear

 Clear H2X Anti-Fog

 Gray

 Amber

 Infinity Blue

 Silver Mirror

 Blue Mirror

 Indoor/Outdoor Mirror

- Economically priced to fit any budget.
- Incredibly light, resilient & durable protective eyewear for all day wear.
- Closefitting unitary front with dual 9.5 base curvature offers wide and unobstructed vision.
- Fashionable design resembles sunglasses, suitable for both men and women.
- Scratch-resistant, hard-coated polycarbonate lens filter out more than 99.9% of harmful UV rays.

GENERAL SPECIFICATION

Bridge: 12mm

Closest Point Between Lens: 8mm

Closest Point Between Temple Tips: 84mm

Lens Base: 9.5 Curve

Lens Size Diagonal: 73mm

Lens Size Vertical: 42mm

Lens Thickness: 2.45mm

Overall Length [Lens-Tip]: 158mm

Overall Width [Hinge-Hinge]: 134mm

PD: 68mm

Weight: 22gm

PACKAGING
Polybag: 1 pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9.5 curve lens, wrap around design with side protection
Frame	N/A	N/A
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula
Hinge	Polycarbonate	3 barrel type, integral to frame/sleeve
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S3210S	 Clear	P Z87 + U6	P Z87 +
S3210ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 +
S3220S	 Gray	P Z87 + U6 L2.5	P Z87 +
S3230S	 Amber	P Z87 + U6	P Z87 +
S3260S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 +
S3270S	 Silver Mirror	P Z87 + S	P Z87 +
S3275S	 Blue Mirror	P Z87 + S	P Z87 +
S3280S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact