# **Setmour**

## **Product Information Sheet**



## **TOOL CRIB CHAIN & CABLE LUBE** #620-1502

A lightweight black lubricant that penetrates deeply and prolongs the life of any size chain or wire by keeping it supple and resisting rust. Displaces water and has excellent clinging properties. Extension tube is provided for pinpoint application. Application should be confined to light duty drive chains not running thru an oil bath.

#### Suggested Uses:

Motorcycles Chain saws Bicycles Elevator cables Link & roller assemblies Sprockets

#### Packaging:

UPC Code Cans per case Shipping weight per case Container Label weight Shipping Classification Hazard Class

### 043281007009

6 9 lbs. 20 fluid ounce can 15 ounces (426 grams) Consumer Commodity ORM-D, UN 1950 2.1

#### **Properties:**

Cleanup	Lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 F
Specific Gravity	0.76
Solids Content	47%
VOC content	44%
HAPs content	13%
Storage Temperature	40-90F
Application Temperature	40-100F
Active Ingredient	Molybdenum Disulfide
Lubricity Rating	Excellent
Appearance	Black, tacky
Operating Speed	2000+ RPM
High Temperature Resister	ice 350F
Low Temperature Resisten	ce -50⊧
Shelf life	Guaranteed for 2 years
Food contact rating	No

Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 Phone:815-895-9101 or 800-435-4482Fax:815-895-8475 or 800-343-4258

www.seymourpaint.com