



TOOL CRIB DRY MOLY LUBE

#620-1505

A quick-drying, thin film that provides superior lubrication under extreme pressures and a broad temperature ranges. Excellent adhesion, oil free, and protects against seizing, fretting, and galling. Provides excellent anti-wear protection for cutting and forming tools. Sprays in any position.

Suggested Uses:

Dust free lubricant for pre-assembly and production
 Wire drawing
 Gasket and stop-off coating
 Rubber mold release
 Machine tool slides
 Conveyors (hi-temperature)

Packaging:

UPC Code	043281007023
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Cleanup	Lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	3%
VOC content	47%, can't exceed 50%
HAPs content	7%
Storage Temperature	40-90F
Application Temperature	40-100F
Active Ingredient	Molybdenum Disulfide
Lubricity Rating	Excellent
Appearance	Black
Operating Speed	2000+ RPM
High Temperature Resistance	600 ^o F
Low Temperature Resistance	-100 ^o F
Heavy Load Capability	Yes
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time:

Not Applicable

Gloss:

None