



## TOOL CRIB DRY GRAPHITE LUBE #620-1506

A fast drying graphite lubricant that reduces friction and noise. Effective under heavy pressures and continuously high temperatures. The oil-free formulation resists water and alkalis. Sprays in any position and an extension tube is provided for pinpoint application.

### Suggested Uses:

Bearings  
gaskets  
Conveyor rollers/chains/hoists/wheels  
Hinges  
Rubber moldings  
Anti-seize thread lubricant

### Packaging:

UPC Code	043281007030
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity, ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Cleanup	Lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 F
Specific Gravity	0.80
Solids Content	3%
VOC content	42%, cannot exceed 50%
HAPs content	22%
Storage Temperature	40-100F
Application Temperature	50-90F
Extreme Pressures	Up to 25,000 PSI
Abrasion Resistance	Excellent
Gas Resistance	No
Heat Resistance	400o F continuous
Active Ingredient	graphite
Shelf life	Guaranteed for 2 years

### Dry Time:

Not Applicable

### Gloss:

None