

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

1 Identification of the substance and manufacturer

Trade name: TOOLMAKER'S BLUE LAYOUT INK
Product code: 0006201558
Recommended use: Paint and coating applications.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Repr. 1B H360 May damage fertility or the unborn child.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 May damage fertility or the unborn child.
 May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	35.22%
74-98-6	propane	13.85%
108-21-4	isopropyl acetate	13.17%
106-97-8	n-butane	8.14%
64-17-5	ethyl alcohol	7.28%
108-88-3	Toluene	3.43%
111-76-2	Glycol Ether EB	3.21%
78-93-3	methyl ethyl ketone	2.9%
67-63-0	Isopropyl Alcohol	2.37%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

(Contd. on page 2)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 1)

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up: Ensure adequate ventilation.
Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm
REL (USA) Long-term value: 590 mg/m³, 250 ppm
TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

108-21-4 isopropyl acetate

PEL (USA) Long-term value: 950 mg/m³, 250 ppm
TLV (USA) Short-term value: 626 mg/m³, 150 ppm
Long-term value: 417 mg/m³, 100 ppm

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm
TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm
(EX)

64-17-5 ethyl alcohol

PEL (USA) Long-term value: 1900 mg/m³, 1000 ppm
REL (USA) Long-term value: 1900 mg/m³, 1000 ppm
TLV (USA) Short-term value: 1880 mg/m³, 1000 ppm

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift
REL (USA) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV (USA) Long-term value: 75 mg/m³, 20 ppm
BEI

111-76-2 Glycol Ether EB

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin
REL (USA) Long-term value: 24 mg/m³, 5 ppm
Skin
TLV (USA) Long-term value: 97 mg/m³, 20 ppm
BEI

78-93-3 methyl ethyl ketone

PEL (USA) Long-term value: 590 mg/m³, 200 ppm
REL (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
TLV (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

(Contd. on page 3)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 2)

REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

111-76-2 Glycol Ether EB

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

78-93-3 methyl ethyl ketone

BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----------	---

67-63-0 Isopropyl Alcohol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	52.9 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

(Contd. on page 4)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 3)

11 Toxicological information**LD/LC50 values that are relevant for classification:****108-21-4 isopropyl acetate**

Oral LD50 9,800 mg/kg (rat)

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

64-17-5 ethyl alcohol

Oral LD50 7,060 mg/kg (rat)

Inhalative LC50/4 h 20,000 mg/l (rat)

111-76-2 Glycol Ether EB

Oral LD50 1,480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

78-93-3 methyl ethyl ketone

Oral LD50 3,300 mg/kg (rat)

Dermal LD50 5,000 mg/kg (rbt)

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat)

Dermal LD50 13,400 mg/kg (rab)

Inhalative LC50/4 h 30 mg/l (rat)

Information on toxicological effects: No data available.**Skin effects:** No irritant effect.**Eye effects:** Irritating effect.**Sensitization:** No sensitizing effects known.**12 Ecological information****Aquatic toxicity:** Hazardous for water, do not empty into drains.**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.**Bioaccumulative potential:** No further relevant information available.**Mobility in soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.**14 Transport information****UN-Number** UN1950**DOT** N/A**DOT** Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

ADR**Transport hazard class(es):****Class** 2.1**Marine pollutant:** No**Special precautions for user:** Warning: Gases**EMS Number:** F-D,S-U**Packaging Group:** --**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

111-76-2 Glycol Ether EB

78-93-3 methyl ethyl ketone

67-63-0 Isopropyl Alcohol

Toxic Substances Control Act**(TSCA):** All hazardous ingredients for this product are found on the inventory list of substances.**Consumer Product Safety****Comission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

100-41-4 ethyl benzene

108-10-1 methyl isobutyl ketone

(Contd. on page 5)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: TOOLMAKER'S BLUE LAYOUT INK

(Contd. of page 4)

**California Proposition 65 chemicals
known to cause birth defects or
reproductive harm:**

67-56-1 Methanol

108-88-3 Toluene

108-10-1 methyl isobutyl ketone

**CANADIAN ENVIRONMENTAL
PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1 Acetone

I

111-76-2 Glycol Ether EB

NL

78-93-3 methyl ethyl ketone

I

16 Other information**Contact:**

Regulatory Affairs