

SPRUCE METALLICS AND LACQUERS



A fast drying lacquer spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our Spruce primers to ensure proper adhesion.

Suggested Uses:

Metal, wood and wicker
Furniture
Toys
Boats
Bikes

Packaging:

Cans per case	12
Shipping weight per case	15 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Specific Gravity	0.86
Solids Content	Glosses: ~12% Flats: ~13% Metallics: ~13%
MIR value	Glosses: 0.86, cannot exceed 0.95 Clear: 0.77, cannot exceed 0.85 Metallics: 1.16, cannot exceed 1.25
HAPs content	Glosses: ~10% Clear: ~27% Metallics: ~25%
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To recoat	20 minutes

*At 7 F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*:	High Gloss, >80
	Semi-Gloss, 40-50
	Flat, <15
	Metallic—Not Applicable

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code	Part #	Description	UPC Code
98-1	Aluminum	043281002356	98-31	Gloss Clear Acrylic	043281002578
98-5	Gold	043281002394	98-32	Dull Aluminum	043281002585
98-14	Copper	043281002455	98-38	Semi-Gloss Black Lacquer	043281002639
98-17	Nickel	043281002486	98-41	Chrome Aluminum	043281002653
98-18	Gloss Black Lacquer	043281002493	98-50	Gold	043281002721
98-30	Flat Black Lacquer	043281002561			