



**Designed for the Pros**




# Our Mission



At ProBuilt Professional Lighting, our mission is to provide the most innovative, durable, best in class, temporary work lights for industrial and commercial applications.

We provide the right lights, allowing you to confidently complete your work in the most challenging lighting conditions. We will continue to innovate and develop new products to change the way you see.

# Our Brands



## Designed for the Pros

# Contents



|          |                                      |           |          |                              |                                 |
|----------|--------------------------------------|-----------|----------|------------------------------|---------------------------------|
| <b>1</b> | <b>Wobblelights</b>                  | <b>5</b>  | <b>5</b> | <b>Tripods</b>               | <b>17</b>                       |
| <b>2</b> | <b>Hang-A-Lights</b>                 |           | <b>6</b> | <b>6</b>                     | <b>Utility Lighting</b>         |
|          | LED Hang-A-Lights                    | 6         |          | Dusk to Dawn Lights          | 18                              |
|          | Magnetic, Fluorescent, Metal Halide  | 7         |          | Magnetic Hang-A-Lights       | 18                              |
|          | String Lights                        | 8         |          | Dock Light                   | 19                              |
| <b>3</b> | <b>Corded Flood Lights</b>           | <b>9</b>  |          | Shop Light                   | 19                              |
|          | Slim Series                          | 10        |          | Drop Light                   | 19                              |
|          | ProLight™ 6000                       | 10        | <b>7</b> | <b>7</b>                     | <b>Handheld &amp; Specialty</b> |
|          | XLE Series                           | 11        |          | Pen Lights                   | 20                              |
|          | Slim Series XL                       | 11        |          | Rechargeable                 | 21                              |
|          | 360° Industrial Light Kit            | 12        |          | Non-Rechargeable             | 22/23                           |
|          | Defender Floor Lights                | 12        |          | Searchlights                 | 24                              |
|          | Eco Uplight                          | 12        |          | HeadLamps                    | 24                              |
| <b>4</b> | <b>Battery Operated Flood Lights</b> | <b>13</b> |          | Intrinsically Safe           | 25                              |
|          | ProLight™ Mini                       | 14        |          | Hand Lamps                   | 26                              |
|          | ProLight™ Max                        | 14        |          | Pulsars                      | 26                              |
|          | ProLight™ 100 Series                 | 14        | <b>8</b> | <b>8</b>                     | <b>Spec Charts</b>              |
|          | ProLight™ 200 Series                 | 14        |          | Handheld Lighting Spec Chart | 27                              |
|          | ProLight™ 30w Folding Light          | 14        |          | Hang-A-Light Fixture Spacing | 28                              |
|          | Galaxy Pro                           | 15        |          | Lighting Layout Tool         | 29                              |
|          | Galaxy 1000                          | 15        |          | IP Ratings Chart             | 30                              |
|          | Galaxy 2000                          | 15        |          | Color Temperature Chart      | 31                              |
|          | MegaStar                             | 16        |          | LED Energy Savings           | 31                              |
|          | Solaris                              | 16        |          |                              |                                 |







## Wobblelight LED V-Series



The Wobblelight® LED V-Series, has the same great patented, self-righting technology with a new look. Still ideal for applications requiring temporary high output lighting for areas up to 75 feet diameter. This new look features an integrated carry handle into the body, LED panel technology and an integrated cord to give the unit a suitable for wet locations rating. The V2 model also has a covered receptacle for interlinking units together.

- Patented Self-Righting Technology
- 360° Lighting
- LED Panel Technology
- Integrated Power Cord
- Integrated Carry Handle
- IP55 Rated
- Dual Thermal Cut-Off to Prevent Over Heating



| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated    | Tested | Cord Type  | IP Rating | Weight |
|-----------|--------|----------------|-----------|-----------|---------|-------|----------|---------------|---------|---------------|--------|------------|-----------|--------|
| 111303LED | 15,000 | 75 ft.         | LED       | 50,000    | 5,000   | 220   | 1.8      | N/A           | 120V    | -40°F - 125°F | cUL    | 16/3 SJOOW | IP55      | 31 lbs |
| 111301LED | 12,000 | 60 ft.         | LED       | 50,000    | 5,000   | 150   | 1.25     | 6 Units Max   | 120V    | -40°F - 125°F | cUL    | 16/3 SJOOW | IP54      | 31 lbs |

## Wobblelight Sr. Series



Made in USA



The patented self-righting Wobblelight® is ideal for applications requiring temporary high-output lighting in areas from 15 to 75 feet diameter. Bright and dependable, the Wobblelight® delivers maximum light output in a highly durable and portable package with no hot surfaces.

### Replacement Bulbs:



500W Halogen  
Model No. 111904



175W/400W Metal Halide  
Model No. 111901/111903



All Wobblelight® models engineered with our patented self-righting design

- Patented Self-Righting Technology
- 360° Lighting
- No Hot Surfaces
- Interlink units together
- Durable

| Model No. | Lumens | Lighting Range | Bulb Type    | Lamp Life | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated | Tested | Cord Type    | Weight |
|-----------|--------|----------------|--------------|-----------|---------|-------|----------|---------------|---------|------------|--------|--------------|--------|
| 111302    | 8,000  | 25 ft.         | Halogen      | 2,000     | 4,000   | 500   | 4.5      | 2             | 120V    | -22°F      | cUL    | Not Included | 28 lbs |
| 111102    | 15,000 | 45 ft.         | Metal Halide | 10,000    | 4,000   | 175   | 1.9      | 5             | 120V    | -22°F      | cUL    | Not Included | 29 lbs |
| 111104    | 40,000 | 75 ft.         | Metal Halide | 20,000    | 4,000   | 400   | 4        | 3             | 120V    | -22°F      | cUL    | Not Included | 33 lbs |

## Wobblelight Jr.® 27"



Made in USA  
CFL Version Only



### Replacement Bulbs:



85 Watt Fluorescent Bulb  
Model No. 111908



80 Watt LED Bulb  
Model No. 111980JR

- Patented Self-Righting Technology
- 360° Lighting
- No Hot Surfaces
- 5' Integrated Power Cord
- Durable

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life | Kelvins | Watts | Amp Draw | Voltage | Temp Rated    | Tested | Cord Type | Weight   |
|-----------|--------|----------------|-------------|-----------|---------|-------|----------|---------|---------------|--------|-----------|----------|
| 111203    | 5,000  | 25 ft.         | Fluorescent | 8,000     | 2,700   | 85    | .6       | 120V    | -20°F - 120°F | cUL    | 18/2 SJTW | 13.5 lbs |
| 111206    | 9,000  | 35 ft.         | LED         | 35,000    | 5,000   | 80    | .7       | 120V    | -40°F - 125°F | cUL    | 18/2 SJTW | 13.9 lbs |



## High Bay LED



When the jobsite demands the maximum overhead light output available, ProBuilt's Hang-A-Light® family is just what is needed. All of these lights offer high-output lighting options and include the durability that you expect from a ProBuilt product. No matter how small or large the area, ProBuilt has a light for the job.

- Replaces 400W metal halide with 60% less energy
- 5' Integrated Power Cord
- No Set-Up Required
- Suitable for DAMP Locations

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated   | Tested | Cord Type | Weight |
|-----------|--------|----------------|-----------|------------|---------|-------|----------|---------------|---------|--------------|--------|-----------|--------|
| 111200LED | 15,000 | 75 ft          | LED       | 50,000 hrs | 5,000   | 150   | 1.6      | N/A           | 120V*   | -40° - 125°F | cUL    | 18/3 SJTW | 18 lbs |

### With Receptacle




- 40 Watt
- 60 Watt
- 80 Watt
- 100 Watt
- 120 Watt
- 150 Watt

### Without Receptacle/Plug



- 40 Watt
- 60 Watt
- 80 Watt
- 100 Watt
- 120 Watt



40w / 111941    60w / 111960    80w / 111980  
100w / 111900    120w / 1119120    150w / 111950

- Covered and Protected LED's
- 360° Lighting
- No Hot Surfaces
- Steel Construction
- Welded Wire Safety Cage

| Model No.  | Lumens | Lighting Range | Bulb Type | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated   | Tested | Cord Type | Weight  |
|------------|--------|----------------|-----------|------------|---------|-------|----------|---------------|---------|--------------|--------|-----------|---------|
| 111040LED  | 5,000  | 20 ft          | LED       | 35,000 hrs | 5,000   | 40    | 0.4      | 10            | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 6 lbs   |
| 111040NR   | 5,000  | 20 ft          | LED       | 35,000 hrs | 5,000   | 40    | 0.4      | N/A           | 120/277 | -40° - 125°F | cUL    | 14/3 SJTW | 6 lbs   |
| 111060LED  | 7,500  | 35 ft          | LED       | 35,000 hrs | 5,000   | 60    | 0.5      | 8             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 6.5 lbs |
| 111060NR   | 7,500  | 35 ft          | LED       | 35,000 hrs | 5,000   | 60    | 0.5      | N/A           | 120/277 | -40° - 125°F | cUL    | 14/3 SJTW | 6.5 lbs |
| 111080LED  | 10,400 | 45 ft          | LED       | 35,000 hrs | 5,000   | 80    | 0.8      | 6             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 7 lbs   |
| 111080NR   | 10,400 | 45 ft          | LED       | 35,000 hrs | 5,000   | 80    | 0.8      | N/A           | 120/277 | -40° - 125°F | cUL    | 14/3 SJTW | 7 lbs   |
| 1110100LED | 13,500 | 50 ft          | LED       | 35,000 hrs | 5,000   | 100   | 0.9      | 4             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 7.5 lbs |
| 1110100NR  | 13,500 | 50 ft          | LED       | 35,000 hrs | 5,000   | 100   | 0.9      | N/A           | 120/277 | -40° - 125°F | cUL    | 14/3 SJTW | 7.5 lbs |
| 1110120LED | 15,600 | 65 ft          | LED       | 35,000 hrs | 5,000   | 120   | 1.1      | 3             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 8 lbs   |
| 1110120NR  | 15,600 | 65 ft          | LED       | 35,000 hrs | 5,000   | 120   | 1.1      | N/A           | 120/277 | -40° - 125°F | cUL    | 14/3 SJTW | 8 lbs   |
| 1110150LED | 19,500 | 75 ft          | LED       | 35,000 hrs | 5,000   | 150   | 1.3      | 3             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 8 lbs   |

## Longneck Series



80w / 111980L  
120w / 1119120L

- Covered and Protected LED's
- Unique "Longneck" bulb shape
- 5' Integrated Power Cord
- 360° Directional Lighting
- Steel Construction
- Spring Loaded Hook
- No Hot Surfaces
- Welded Wire Safety Cage

| Model No.  | Lumens | Lighting Range | Bulb Type | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated   | Tested | Cord Type | Weight   |
|------------|--------|----------------|-----------|------------|---------|-------|----------|---------------|---------|--------------|--------|-----------|----------|
| 111080ECO  | 7,600  | 25 ft          | LED       | 25,000 hrs | 5,000   | 80    | 0.8      | 6             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 5.35 lbs |
| 1110120ECO | 13,500 | 50 ft          | LED       | 30,000 hrs | 5,000   | 120   | 0.9      | 4             | 120V*   | -40° - 125°F | cUL    | 14/3 SJTW | 8 lbs    |

\*Modifiable to 277V





The Hang-A-Light® Magnetic Work Lights are cUL listed for use in wet locations which makes them ideal for tank washing, machine shops or any confined space. It is energy efficient; with a heavy duty earth magnet on the back allowing this light to be attached to metal surfaces or the light can be hung by the eye hooks on the back.

- 6" Heavy Duty Earth Magnet
- Eye Hooks for Hanging
- 5' Integrated Power Cord
- No Exposed Glass
- No Hot Surfaces

42w / 111984

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life  | Kelvins | Watts | Amp Draw | Voltage | Temp Rated   | Tested | Cord Type | IP Rating | Weight |
|-----------|--------|----------------|-------------|------------|---------|-------|----------|---------|--------------|--------|-----------|-----------|--------|
| 111084    | 6,400  | 30 ft          | Fluorescent | 20,000 hrs | 3,500   | 84    | .76      | 120V    | -5° - 120°F  | cUL    | 14/3 SJTW | 65        | 10 lbs |
| 111085    | 6,000  | 30 ft          | LED         | 40,000 hrs | 5,000   | 60    | .54      | 120V    | -30° - 120°F | cUL    | 14/3 SJTW | 65        | 10 lbs |



105w / 111915

This 105 watt spiral fluorescent temporary lighting fixture produces 360° of light with low-cost operation. The integrated 5 foot power cord and spring loaded, steel safety hook make for fast installation. With a built in electrical receptacle and no heavy external ballast, the Hang-A-Light® 105 watt spiral fluorescent takes portability and ease of use to a new level.

- Flicker Free
- 360° Lighting
- Damp Location Use
- Interlink units together
- Welded Wire Safety Cage
- 5' Integrated Power Cord
- Spring Loaded Clamp

Model: 111105F

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated | Tested          | Cord Type | Weight |
|-----------|--------|----------------|-------------|------------|---------|-------|----------|---------------|---------|------------|-----------------|-----------|--------|
| 111105F   | 6,900  | 30 ft          | Fluorescent | 10,000 hrs | 4,000   | 105   | .87      | 6             | 120V*   | 5° - 125°F | cUL/ EnergyStar | 14/3 SJTW | 5 lbs  |



400w / 111903PS

This Hang-A-Light® 400 watt Metal Halide temporary lighting fixture produces 360° of light. The integrated 5 foot power cord and spring loaded, steel safety hook make for fast installation. The heavy gauge steel safety case has an added bottom guard for protection and durability.

- Steel Construction
- 360° Lighting
- Damp Location Use
- Welded Wire Safety Cage
- 6' Integrated Power Cord
- Spring Loaded Clamp

Model: 111400PS

| Model No. | Lumens | Lighting Range | Bulb Type    | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated   | Tested | Cord Type | Weight |
|-----------|--------|----------------|--------------|------------|---------|-------|----------|---------------|---------|--------------|--------|-----------|--------|
| 111400PS  | 42,000 | 100 ft         | Metal Halide | 20,000 hrs | 4,100   | 400   | 4        | Modifiable    | 120V*   | -22° - 120°F | cUL    | 14/3 SJTW | 20 lbs |

\*Modifiable to 277V





The Hang-A-Light® String Light Series is ideal for applications requiring overhead temporary high-output lighting over long distances. The 14/2, 14/3 and 12/3 cords have 5 or 10 sockets with up to 14 watts per socket and are spaced every 5 or 10 feet with plastic or metal cages for bulb protection. Bright and dependable, Hang-A-Light® delivers maximum light output in a durable package with no hot surfaces.

- Protective Plastic Cage
- Energy Efficient
- No Hot Surfaces
- Link Strings Together\*

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Kelvins | Watts  | Amp Draw | Voltage | Linking Units | Tested | Cord Type | Weight |
|-----------|--------|----------------|-----------|-----------------|---------|--------|----------|---------|---------------|--------|-----------|--------|
| 11107050  | N/A    | 50 ft          | N/A       | N/A             | N/A     | 14 x5  | N/A      | 120V    | 8             | UL     | 14/3 SJTW | 10 lbs |
| 11107100  | N/A    | 100 ft         | N/A       | N/A             | N/A     | 14 x10 | N/A      | 120V    | 5             | UL     | 14/3 SJTW | 20 lbs |
| 11108100  | N/A    | 100 ft         | N/A       | N/A             | N/A     | 14 x10 | N/A      | 120V    | N/A           | UL     | 14/2 SJTW | 20 lbs |

\*Only on Models 11107050 & 11107100



LED / 111917

- Protective Plastic Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs
- Link Strings Together
- 14/3 SJTW Cord

| Model No. | Lumens    | Lighting Range | Bulb Type | Lamp Life (hrs) | Kelvins | Watts  | Amp Draw | Voltage | Linking Units | Tested | Cord Type | Weight |
|-----------|-----------|----------------|-----------|-----------------|---------|--------|----------|---------|---------------|--------|-----------|--------|
| 131050    | 1,500 x5  | 50 ft          | LED       | 30,000          | 5,000   | 14 x5  | .64      | 120V    | 8             | UL     | 14/3 SJTW | 10 lbs |
| 131100    | 1,500 x10 | 100 ft         | LED       | 30,000          | 5,000   | 14 x10 | 1.27     | 120V    | 5             | UL     | 14/3 SJTW | 20 lbs |
| 111100    | 1,500 x10 | 100 ft         | LED       | 30,000          | 5,000   | 14 x10 | 1.27     | 120V    | N/A           | UL     | 14/2 SJTW | 20 lbs |

- Protective Metal Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs Available
- Link up to 5 Strings
- 12/3 SJTW Cord



| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Kelvins | Watts  | Amp Draw | Voltage | Linking Units | Tested | Cord Type | Weight |
|-----------|--------|----------------|-----------|-----------------|---------|--------|----------|---------|---------------|--------|-----------|--------|
| 11109050  | N/A    | 50 ft          | N/A       | N/A             | N/A     | 14 x5  | N/A      | 120V    | 5             | cUL    | 12/3 STW  | 13 lbs |
| 11109100  | N/A    | 100 ft         | N/A       | N/A             | N/A     | 14 x10 | N/A      | 120V    | 5             | cUL    | 12/3 STW  | 28 lbs |

- Protective Metal Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs
- Link Strings Together
- 12/3 SJTW Cord



LED / 111917

| Model No. | Lumens    | Lighting Range | Bulb Type | Lamp Life (hrs) | Kelvins | Watts  | Amp Draw | Voltage | Linking Units | Tested | Cord Type | Weight |
|-----------|-----------|----------------|-----------|-----------------|---------|--------|----------|---------|---------------|--------|-----------|--------|
| 121050    | 1,500 x5  | 50 ft          | LED       | 30,000          | 5,000   | 14 x5  | .64      | 120V    | 8             | cUL    | 12/3 STW  | 13 lbs |
| 121100    | 1,500 x10 | 100 ft         | LED       | 30,000          | 5,000   | 14 x10 | 1.27     | 120V    | 5             | cUL    | 12/3 STW  | 28 lbs |







### Slim Series



Compact at only a 1-3/4" max depth and extremely lightweight, the ProLight™ Slim Line LED Floodlight Series are extremely durable. The units are IP65 rated and suitable for use in all weather conditions. Cool operation enables the Slim Line Series to be used in confined spaces, making it ideal for the Construction, Industrial/MRO, Utilities, Transportation and Environmental channels.

- Pure white light
- IP65 Rated
- 5' integrated power cord
- Alloy Aluminum body
- No hot surfaces
- Multiple mounting options

| Model No. | Lumens   | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                    | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type  | Weight   | IP Rating |
|-----------|----------|----------------|-----------|-----------------|-----------------------------|---------|-------|----------|---------|------------|--------|------------|----------|-----------|
| 411015    | 1,500    | 20 ft          | LED       | 50,000          | Floor Stand                 | 5,000   | 15    | .25      | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 2.2 lbs  | 65        |
| 411215    | 1,500    | 20 ft          | LED       | 50,000          | Tripod (311001)             | 5,000   | 15    | .25      | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 9.7 lbs  | 65        |
| 411315    | 1,500 x2 | 30 ft          | LED       | 50,000          | Dual Head w/Tripod (311006) | 5,000   | 15 x2 | .25 x2   | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 11.9 lbs | 65        |
| 411030    | 3,000    | 35 ft          | LED       | 50,000          | Floor Stand                 | 5,000   | 30    | .5       | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 4 lbs    | 65        |
| 411230    | 3,000    | 35ft           | LED       | 50,000          | Tripod (311006)             | 5,000   | 30    | .5       | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 11.5 lbs | 65        |
| 411330    | 3,000 x2 | 45 ft          | LED       | 50,000          | Dual Head w/Tripod (311006) | 5,000   | 30 x2 | .5 x2    | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 15.5 lbs | 65        |
| 411430    | 3,000    | 35 ft          | LED       | 50,000          | Magnet Base                 | 5,000   | 30    | .5       | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 6 lbs    | 65        |
| 411050    | 5,000    | 50 ft          | LED       | 50,000          | Floor Stand                 | 5,000   | 50    | .75      | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 5.4 lbs  | 65        |
| 411250    | 5,000    | 50 ft          | LED       | 50,000          | Tripod                      | 5,000   | 50    | .75      | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 5.4 lbs  | 65        |
| 411350    | 5,000 x2 | 60 ft          | LED       | 50,000          | Dual Head w/Tripod (311006) | 5,000   | 50 x2 | .75 x2   | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 19.3 lbs | 65        |
| 411450    | 5,000    | 50 ft          | LED       | 50,000          | Magnet Base                 | 5,000   | 50    | .75      | 120     | -40°-122°F | cUL    | 18/3 SJWTW | 7.4 lbs  | 65        |

### ProLight™ 6000 Series



The new 42 watt LED ProLight™ 6000 Series produces 6,000 lumens due to the energy efficient, high-output LEDs utilized. Drawing only .4 amps and rated as IP55 for outdoor use, the ProLight™ 6000 can keep the job site safe and bright while providing the ultimate energy savings. Developed for the professional tradesman, the ABS housing and polycarbonate lens make this light durable enough for even the harshest conditions.

- Sealed on/off switch
- Polycarbonate Lens
- Protective ABS Housing
- IP55 Rated
- No hot surfaces
- Multiple mounting options

| Model No. | Lumens   | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                       | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type  | Weight   | IP Rating |
|-----------|----------|----------------|-----------|-----------------|--------------------------------|---------|-------|----------|---------|------------|--------|------------|----------|-----------|
| 515100    | 6,000    | 30 ft          | LED       | 30,000          | Head Only                      | 5,000   | 42    | .4       | 120     | -40°-120°F | cUL    | 16/2 SJWTW | 4.6 lbs  | 55        |
| 515101    | 6,000    | 30 ft          | LED       | 30,000          | Floor Stand                    | 5,000   | 42    | .4       | 120     | -40°-120°F | cUL    | 16/2 SJWTW | 6.4 lbs  | 55        |
| 515102    | 6,000    | 30 ft          | LED       | 30,000          | Magnetic Sled                  | 5,000   | 42    | .4       | 120     | -40°-120°F | cUL    | 16/2 SJWTW | 7.7 lbs  | 55        |
| 515103    | 6,000    | 60 ft          | LED       | 30,000          | Single Head w/ Tripod (311006) | 5,000   | 42    | .4 x2    | 120     | -40°-120°F | cUL    | 16/2 SJWTW | 13.1 lbs | 55        |
| 515104    | 6,000 x2 | 50 ft          | LED       | 30,000          | Dual Head w/ Tripod (311007)   | 5,000   | 42    | .4 x2    | 120     | -40°-120°F | cUL    | 16/2 SJWTW | 14.1 lbs | 55        |



## ProLight™ XLE Series



This 50 watt LED work light produces 6,500 lumens due to the extreme energy efficiency and concentrated high-output LEDs utilized. With no hot surfaces, the ProBuilt XLE Series can keep the job site safe and bright while only drawing 1.4 Amps, providing the ultimate energy savings. Tested and rated to the highest standards, the ProBuilt XLE Series is cUL listed for wet locations and has an IP65 rated housing. Developed for the professional tradesman, the aluminum and steel construction make the ProBuilt XLE Series durable enough for the harshest conditions.

- Sealed on/off switch
- Alloy Aluminum body
- Tempered glass
- No hot surfaces
- 5' integrated power cord
- Multiple mounting options

| Model No. | Lumens   | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                     | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type | Weight   | IP Rating |
|-----------|----------|----------------|-----------|-----------------|------------------------------|---------|-------|----------|---------|------------|--------|-----------|----------|-----------|
| 111500    | 6,500    | 30 ft          | LED       | 50,000          | Floor Stand                  | 5,000   | 50    | 1.4      | 120     | -30°-120°F | cUL    | 18/3 SJTW | 9 lbs    | 65        |
| 111505    | 6,500    | 30 ft          | LED       | 50,000          | Tripod (311006)              | 5,000   | 50    | 1.4      | 120     | -30°-120°F | cUL    | 18/3 SJTW | 16.5 lbs | 65        |
| 111507    | 6,500    | 30 ft          | LED       | 50,000          | Magnet                       | 5,000   | 50    | 1.4      | 120     | -30°-120°F | cUL    | 18/3 SJTW | 11 lbs   | 65        |
| 111000    | 6,500 x2 | 60 ft          | LED       | 50,000          | Dual Head                    | 5,000   | 50 x2 | 1.4 x2   | 120     | -30°-120°F | cUL    | 18/3 SJTW | 20 lbs   | 65        |
| 111005    | 6,500 x2 | 60 ft          | LED       | 50,000          | Dual Head w/ Tripod (311007) | 5,000   | 50 x2 | 1.4 x2   | 120     | -30°-120°F | cUL    | 18/3 SJTW | 33 lbs   | 65        |

## ProLight™ Slim Series Extreme



The newest addition to the ProBuilt floodlight category are the Slim Series XL! With three high wattages of 150w, 220w and 300w, these lights are energy efficient and have a high-output of Lumens topping out at 30,000! Due to the extreme slim design and the cool operation these lights can be used in confined spaces. The new lights are also designed for permanent installation or long-term temporary use outdoors. The ProLight™ Slim Series XL can keep the job site safe and bright while drawing minimal amps, providing the ultimate energy savings. Tested and rated to the highest standards, the ProLight™ Slim Series XL is cUL listed for wet locations and has an IP65 rated housing. Developed for the professional tradesman, the aluminum and steel construction make the ProLight™ Slim Series XL durable enough for the harshest conditions.

- High Wattage/High Output
- Pure white light
- IP65 Rated
- 5' integrated power cord
- Alloy Aluminum body
- No hot surfaces

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type | Weight   | IP Rating |
|-----------|--------|----------------|-----------|-----------------|---------|-------|----------|---------|------------|--------|-----------|----------|-----------|
| 4110150   | 15,000 | 70 ft          | LED       | 50,000 hrs      | 5,000   | 150   | 1.36     | 100-277 | -40°-105°F | cUL    | 18/3 SJTW | 12.2 lbs | 65        |
| 4110220   | 22,000 | 90 ft          | LED       | 50,000 hrs      | 5,000   | 220   | 2        | 100-277 | -40°-104°F | cUL    | 18/3 SJTW | 17.2 lbs | 65        |
| 4110300   | 30,000 | 120 ft         | LED       | 50,000 hrs      | 5,000   | 300   | 2.7      | 100-277 | -40°-104°F | cUL    | 18/3 SJTW | 19.7 lbs | 65        |

## ProLight™ 360° Industrial Light Kit



The ProLight™ 360° Industrial LED Light Kit produces 15,000 total lumens. This light gives the option to be a full 360° light or a 180° light by utilizing two independent switches on the bottom of the base, each side producing 7,500 lumens. With no hot surfaces, the ProLight™ 360° Industrial Light can keep the job site safe and bright while only drawing .7 Amps per side and only 1.4 when fully powered, providing ultimate energy savings. Tested and rated to the highest standards, the ProLight™ 360° Industrial Light is cUL listed for wet locations and has an IP65 rated housing. What's more is this light is packed with all of your needs in mind. The kit comes with a floor stand, two rare-earth magnets, a hook for hanging overhead and a tripod adapter. Developed for the professional tradesman, the steel construction makes the ProLight™ 360° Industrial Light durable enough for the harshest conditions.

- 360° LED Lighting
- Independent 180° Lighting
- Durable and Versatile
- IP65 Rated
- 5' integrated power cord
- No hot surfaces
- Pure white light
- Multiple mounting options

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Features   | Kelvins | Watts | Amp Draw | Voltage | Temp Rated     | Tested | Cord Type    | Weight | IP Rating |
|-----------|--------|----------------|-----------|-----------------|--|---------|-------|----------|---------|----------------|--------|--------------|--------|-----------|
| 111508    | 15,000 | 40 ft          | LED       | 50,000          | Included: Floor Stand<br>Tripod Mount, Hook,<br>Two Earth Magnets                      | 5,000   | 120   | .7 x2    | 120     | -30°-<br>120°F | cUL    | 18/3<br>SJTW | 13 lbs | 65        |
| 111509    | 15,000 | 40 ft          | LED       | 50,000          | Included: Floor Stand<br>Tripod Mount, Hook,<br>Two Earth Magnets<br>Heavy Duty Tripod | 5,000   | 120   | .7 x2    | 120     | -30°-<br>120°F | cUL    | 18/3<br>SJTW | 23 lbs | 65        |

## Defender Floor Lights



Portable, lightweight and durable, the Defender® Floor Lights deliver big brightness from a small package. Heavy-duty impact resistant housing keeps them on the job. Compact size goes into tight places and stores easily.



- Polycarbonate Lens
- Rubberized handle/base
- 10' integrated power cord

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life (hrs) | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type | Weight | IP Rating |
|-----------|--------|----------------|-------------|-----------------|---------|-------|----------|---------|------------|--------|-----------|--------|-----------|
| E709165   | 2,850  | 15 ft          | Fluorescent | 10,000          | 2,700   | 38    | .35      | 120     | -4°-140°F  | CSA    | 16/2 SJT  | 4 lbs  | 44        |
| E709166   | 1,300  | 15 ft          | LED         | 45,000          | 5,000   | 14    | .13      | 120     | -4°-140°F  | CSA    | 16/2 SJT  | 4 lbs  | 44        |

## Eco Uplight

The Defender® Eco Uplight is the ultimate tripod task light for durability, portability and versatility. Available in a 4 foot version, the integrated and collapsible legs open up to 30" diameter for exceptional stability. This low-current, high-output light tackles many tasks that other products can't, including use in confined spaces.



- 10 amp power receptacle
- Collapsible, locking tripod base
- Link Multiple Units
- Non-Slip Feet

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life (hrs) | Height | Kelvins | Watts | Amp Draw | Voltage | Temp Rated    | Tested | Cord Type    | Weight | IP Rating |
|-----------|--------|----------------|-------------|-----------------|--------|---------|-------|----------|---------|---------------|--------|--------------|--------|-----------|
| E712600   | 3,250  | 15 ft          | Fluorescent | 20,000          | 4 ft   | 4,000   | 36    | .33      | 120     | -4°-<br>140°F | CSA    | 18/3<br>SJTW | 10 lbs | 44        |





## ProLight™ Mini & Max



The ProLight™ Mini & Max are light weight, portable, innovative, high-powered, LED Flood Lights delivering up to 1,800 Lumens with the Max. Featuring a 110° pivoting head allowing for a bright white floodlight beam and an even spread of light, an on/off switch, three modes: high, low and strobe as well as magnetic feet. The ProLight™ Mini & Max can also be mounted to an optional tripod for optimal light positioning. The Lithium-Ion battery provides power for 10 hours on low and 5 hours on high and requires no maintenance.

- IP65 Rated
- Up to 10 hrs run time
- Magnetic Feet
- 110° Pivoting Head
- Li-Ion Rechargeable Battery
- No hot surfaces
- Multiple mounting options

| Model No. | Lumens                  | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                 | Kelvins | Watts | Temp Rated      | Tested | Battery Type                 | Run Time                 | Recharge Time | Weight  | IP Rating |
|-----------|-------------------------|----------------|-----------|-----------------|--------------------------|---------|-------|-----------------|--------|------------------------------|--------------------------|---------------|---------|-----------|
| 511510    | 900 High<br>450 Low     | 12 ft          | LED       | 40,000          | Magnetic Feet<br>3 Modes | 5,000   | 10    | -10° -<br>125°F | cUL    | Rechargeable<br>4.4Ah Li-Ion | 5 hrs high<br>10 hrs low | 5 hrs         | 2.2 lbs | 65        |
| 511512    | 1,800 High<br>1,000 Low | 25 ft          | LED       | 40,000          | Magnetic Feet<br>3 Modes | 5,000   | 20    | -10° -<br>125°F | cUL    | Rechargeable<br>8.8Ah Li-Ion | 5 hrs high<br>10 hrs low | 5 hrs         | 3 lbs   | 65        |

## ProLight™ 100 & 200



The ProLight™ 100 & ProLight™ 200 are the first of their kind for ProBuilt with a removable, rechargeable battery. 3 modes combined with magnetic feet, LED technology, IP65 rated and a USB charging port gives you the versatility to work in any conditions. The ProLight™ 100 delivers 800 lumens on high, while delivering 400 lumens on medium and 200 lumens on low. The ProLight™ 200 delivers 1,700 lumens on high, 850 lumens on medium and 425 lumens on low.

- IP65 Rated
- Up to 12 hrs run time
- Magnetic Feet
- 180° Pivoting Head
- Li-Ion Removeable Rechargeable Battery
- USB Charging Port
- LED Indicator Light

| Model No. | Lumens      | Lighting Range | Bulb Type | Lamp Life (hrs) | Features   | Kelvins | Watts | Temp Rated      | Tested | Battery Type                      | Run Time (hrs) | Recharge Time | Weight   | IP Rating |
|-----------|-------------|----------------|-----------|-----------------|--|---------|-------|-----------------|--------|-----------------------------------|----------------|---------------|----------|-----------|
| 516001    | 800 (Max)   | 12 ft          | LED       | 50,000          | 3 Modes<br>Magnetic Feet<br>Removable/Rechargeable Battery | 5,000   | 10    | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 4.4Ah | 3 / 6 / 12     | 5 hrs         | 2.24 lbs | 65        |
| 516002    | 800 (Max)   | 12 ft          | LED       | 50,000          | USB Charging Port<br>LED Battery Indicator                 | 5,000   | 10    | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 4.4Ah | 3 / 6 / 12     | 5 hrs         | 2.24 lbs | 65        |
| 516003    | 1,700 (Max) | 25 ft          | LED       | 50,000          | Kit Option w/ Two Batteries<br>and Carrying Bag            | 5,000   | 20    | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 8.8Ah | 3 / 6 / 12     | 5 hrs         | 2.24 lbs | 65        |
| 516004    | 1,700 (Max) | 25 ft          | LED       | 50,000          |  | 5,000   | 20    | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 8.8Ah | 3 / 6 / 12     | 5 hrs         | 2.24 lbs | 65        |
| 416003    | N/A         | N/A            | N/A       | N/A             | Small ProLight™ Shop Bag                                   | N/A     | N/A   | N/A             | N/A    | N/A                               | N/A            | N/A           | N/A      | N/A       |
| 416004    | N/A         | N/A            | N/A       | N/A             | Large ProLight™ Shop Bag                                   | N/A     | N/A   | N/A             | N/A    | N/A                               | N/A            | N/A           | N/A      | N/A       |
| 416001    | N/A         | N/A            | N/A       | N/A             | 7.4V 4.4Ah Battery Only                                    | N/A     | N/A   | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 4.4Ah | 3 / 6 / 12     | 5 hrs         | .76 lbs  | 65        |
| 416002    | N/A         | N/A            | N/A       | N/A             | 7.4V 8.8Ah Battery Only                                    | N/A     | N/A   | -10° -<br>125°F | cUL    | Rechargeable<br>Li-Ion 7.4v 8.8Ah | 3 / 6 / 12     | 5 hrs         | 1 lbs    | 65        |

## ProLight™ 30W Folding Light



The ProLight™ 30 watt rechargeable folding work light has been designed for indoor and outdoor use on work sites where a power source is not readily available. 4 modes combined with the folding portability gives you multiple options of light. Powerful LEDs give you a light output of 2,400 lumens at full power, 1,200 lumens on half power and 800 lumens at 30% power. There is also the fourth mode of dimmable giving you anywhere from 450 lumens to the max of full power.

- IP65 Rated
- Up to 8 hrs run time
- 3 Modes
- No hot surfaces
- Li-Ion Rechargeable Battery
- Opens out to 180°
- Multiple Position Options

| Model No. | Lumens                              | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                              | Kelvins | Watts | Temp Rated      | Tested | Battery Type                                    | Run Time (hrs) | Recharge Time | Weight  | IP Rating |
|-----------|-------------------------------------|----------------|-----------|-----------------|---------------------------------------|---------|-------|-----------------|--------|---|----------------|---------------|---------|-----------|
| 514124    | 2,400 Full<br>1,200 Half<br>800 30% | 32 ft          | LED       | 50,000          | Wall Charger<br>Car Charger           | 6,500   | 30    | -10° -<br>125°F | cUL    | Rechargeable<br>7.4V 8800mAh<br>Lithium Battery | 2.5 / 5 / 8    | 4 hrs         | 4.6 lbs | 65        |
| 514125    | 2,400 Full<br>1,200 Half<br>800 30% | 32 ft          | LED       | 50,000          | Wall Charger<br>Car Charger<br>Tripod | 6,500   | 30    | -10° -<br>125°F | cUL    | Rechargeable<br>7.4V 8800mAh<br>Lithium Battery | 2.5 / 5 / 8    | 4 hrs         | 4.6 lbs | 65        |



## NightSearcher® Galaxy Pro



The Galaxy Pro rechargeable LED Floodlight, designed using the toughest composite materials for use in industrial applications where it is essential to have robust, maintenance free products. Utilizing the very latest LED technology the Galaxy Pro produces a very impressive 3,500 Lumens output (equivalent to a 500W Halogen light) and gives a wide floodlight beam in excess of 49 feet.

- 3 Modes
- Li-Ion Rechargeable Battery
- Rechargeable
- No hot surfaces
- IP54
- 180° Pivoting Head
- Multiple mounting options



\*Optional tripod available 311001

\*Optional magnetic feet kit available 514103

| Model No. | Lumens                  | Lighting Range | Bulb Type | Lamp Life (hrs) | Features          | Kelvins | Watts | Temp Rated     | Tested | Battery Type                | Run Time                | Recharge Time | Weight  | IP Rating |
|-----------|-------------------------|----------------|-----------|-----------------|-------------------|---------|-------|----------------|--------|-----------------------------|-------------------------|---------------|---------|-----------|
| 514100    | 3,500 High<br>1,750 Low | 49 ft          | LED       | 50,000          | 3 Modes           | 5,000   | 30    | -20°-<br>140°F | CE     | Rechargeable<br>7.4V Li-Ion | 4 hrs high<br>8 hrs low | 8 hrs         | 3.4 lbs | 54        |
| 514104    | 3,500 High<br>1,750 Low | 49 ft          | LED       | 50,000          | 3 Modes<br>Tripod | 5,000   | 30    | -20°-<br>140°F | CE     | Rechargeable<br>7.4V Li-Ion | 4 hrs high<br>8 hrs low | 8 hrs         | 3.4 lbs | 54        |

## NightSearcher® Galaxy 1000

The Galaxy 1000 LED portable rechargeable work light is ideal for inspection and other tasks where a lightweight portable solution is required. It has a 360° movement thanks to the adjustable bracket and two modes (high and low). The 1000 will give 1,000 lumens on high and 500 on low.

- IP54 Rated
- Li-Ion Rechargeable Battery
- 360° Movement
- No hot surfaces
- Fold flat design for compact storage
- Multiple mounting options



| Model No. | Lumens                | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                 | Kelvins | Tested | Battery Type                         | Run Time                    | Recharge Time | Weight  | IP Rating |
|-----------|-----------------------|----------------|-----------|-----------------|--------------------------|---------|--------|--------------------------------------|-----------------------------|---------------|---------|-----------|
| 514101    | 1,000 High<br>500 Low | 32 ft          | LED       | 40,000          | 360° Movement<br>2 Modes | 5,000   | CE     | Rechargeable 7.4V<br>1800 mAh Li-Ion | 1.4 hrs high<br>3.2 hrs low | 8 hrs         | 1.2 lbs | 54        |

## NightSearcher® Galaxy 2000

The Galaxy 2000 LED portable rechargeable work light is ideal for inspection and other tasks where a lightweight portable solution is required. It has a 360° movement thanks to the adjustable bracket and two modes (high and low). The Galaxy 2000 will give 2,000 lumens on high and 1,000 lumens on low.

- IP54 Rated
- Li-Ion Rechargeable Battery
- 360° Movement
- No hot surfaces
- Fold flat design for compact storage
- Multiple mounting options



| Model No. | Lumens                  | Lighting Range | Bulb Type | Lamp Life (hrs) | Features                 | Kelvins | Tested | Battery Type                         | Run Time                | Recharge Time | Weight | IP Rating |
|-----------|-------------------------|----------------|-----------|-----------------|--------------------------|---------|--------|--------------------------------------|-------------------------|---------------|--------|-----------|
| 514102    | 2,000 High<br>1,000 Low | 65 ft          | LED       | 40,000          | 360° Movement<br>2 Modes | 5,000   | CE     | Rechargeable 7.4V<br>4800 mAh Li-Ion | 2 hrs high<br>4 hrs low | 8 hrs         | 2 lbs  | 54        |

## NightSearcher® MegaStar LED




The SOLARIS Megastar is designed for temporary floodlighting large areas; eight units will illuminate a 195x130ft area. This can easily be set up in under 2 minutes and used anywhere. The lightweight aluminum tripod has double extending safety locking sections that can be secondarily secured using the attached locking pins.

The tripod locks into the power pack utilizing the weight of the power pack to give stability to the light and tripod. Lightweight, easy to carry / transport and store. Quick and easy to assemble and of robust weatherproof construction, suitable for emergency services, military and construction sites.

- Up to 16,000 lumens
- Rechargeable
- 3 Power Options
- Adjustable 3 section w/ safety locking pins
- Tough, impact resistant ABS plastic casing
- No hot surfaces
- IP44

### Light Coverage



| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Features           | Kelvins | Temp Rated | Tested | Battery Type               | Run Time | Recharge Time | Weight | IP Rating |
|-----------|--------|----------------|-----------|-----------------|--------------------|---------|------------|--------|----------------------------|----------|---------------|--------|-----------|
| 511939    | 16,000 | 164 ft         | LED       | 50,000          | 4 Modes Adjustable | 5,000   | -20°-140°F | CE     | Rechargeable 12V /35Ah SLA | 3.5 hrs  | 10 hrs        | 54 lbs | 44        |
|           | 8,000  | 123 ft         |           |                 |                    |         |            |        |                            | 7 hrs    |               |        |           |
|           | 4,000  | 82 ft          |           |                 |                    |         |            |        |                            | 14 hrs   |               |        |           |
|           | 2,000  | 41 ft          |           |                 |                    |         |            |        |                            | 28 hrs   |               |        |           |


## NightSearcher® Solaris LED

The SOLARIS LITE range uses the latest in LED technology and thermal power management, providing intense light power in a compact portable unit. This unit can be set up in less than 1 minute for rapid deployment in emergency situations, and is made from a very tough ABS plastic to ensure long operating life and reliability for all situations.


The SOLARIS DUO offers a real alternative to generator powered lights, offering a very high light output up to 32,000 lumens. It is lightweight and all parts are housed in a highly durable plastic case. It has wheels and pull-up handle for easy transportation. The DUO has telescopic poles reaching to 6 feet and is stable due to the retractable stability legs.



### Light Coverage



### Light Coverage



| Model No.  | Lumens | Lighting Range | Bulb Type | Lamp Life (hrs) | Features           | Kelvins | Temp Rated | Tested | Battery Type                    | Run Time | Recharge Time | Weight   | IP Rating |
|------------|--------|----------------|-----------|-----------------|--------------------|---------|------------|--------|---------------------------------|----------|---------------|----------|-----------|
| 511000LITH | 16,000 | 164 ft         | LED       | 50,000          | 4 Modes Adjustable | 5,000   | -20°-140°F | CE     | Rechargeable 14.8V /18Ah Li-Ion | 2 hrs    | 7 hrs         | 12.5 lbs | 65        |
|            | 8,000  | 123 ft         |           |                 |                    |         |            |        |                                 | 4 hrs    |               |          |           |
|            | 4,000  | 82 ft          |           |                 |                    |         |            |        |                                 | 8 hrs    |               |          |           |
|            | 2,000  | 41 ft          |           |                 |                    |         |            |        |                                 | 16 hrs   |               |          |           |
| 512000LITH | 32,000 | 164 ft         | LED       | 50,000          | 4 Modes Adjustable | 5,000   | -20°-140°F | CE     | Rechargeable 14.8V /36Ah Li-Ion | 2 hrs    | 4 hrs         | 42.3 lbs | 65        |
|            | 16,000 | 123 ft         |           |                 |                    |         |            |        |                                 | 4 hrs    |               |          |           |
|            | 8,000  | 82 ft          |           |                 |                    |         |            |        |                                 | 8 hrs    |               |          |           |
|            | 4,000  | 41 ft          |           |                 |                    |         |            |        |                                 | 16 hrs   |               |          |           |



## ProLight™ Standard Tripod



The ProLight™ Standard Tripod extends up to 5 feet and is great for pairing with the 15W Slim Series Single Head, the Galaxy Pro, the ProLight™ Mini 10W LED and the ProLight™ Max 20W LED Rechargeable Lights as well as the ProLight™ 30W Folding Work Light, Galaxy 1000 and 2000.

| Model No. | Features   | Weight  | Max Height |
|-----------|------------|---------|------------|
| 311001    | Adjustable | 7.5 lbs | 5 ft       |

## ProLight™ 2-Stage Tripod

The ProLight™ 2-Stage Tripod extends up to 5 feet and is great for pairing with the 15W Slim Series Dual Head, the 30 and 50W Slim Series Single Head as well as the 30W Dual Head utilizing the included crossbar. This stand also pairs well with the ProLight™ XLE Series Single Head and the NightSearcher® LED 6000.

| Model No. | Features   | Weight  | Max Height |
|-----------|------------|---------|------------|
| 311006    | Adjustable | 8.5 lbs | 5 ft       |



## ProLight™ Heavy Duty Tripod



The ProLight™ Heavy Duty Tripod extends up to 6 feet and is great for pairing with the ProLight™ XLE Series Dual Head as well as the ProLight™ 360° Industrial Light. This tripod also comes with a crossbar for additional pairing.

| Model No. | Features   | Weight  | Max Height |
|-----------|------------|---------|------------|
| 311007    | Adjustable | 9.5 lbs | 6 ft       |

### ProBuilt Tripod Matrix

| 311001 - Standard |   | 311006 - 2-Stage |  | 311007 - Heavy Duty |                                     |
|-------------------|---|------------------|--|---------------------|-------------------------------------|
| 411215            | Slim Series 15-Watt LED Single Head             | 411315           | Slim Series 15-Watt LED Dual Head            | 111005              | ProLight XLE Series Dual Head       |
| 511510            | ProLight Mini 10W LED Light                     | 411230           | Slim Series 30-Watt LED Single Head          | 111508              | 360° Industrial Light Kit           |
| 511512            | ProLight Max 20W LED Light                      | 411330           | Slim Series 30-Watt LED Dual Head            | 111509              | 360° Industrial Light Kit w/ Tripod |
| 514100            | Galaxy Pro                                      | 411250           | Slim Series 50-Watt LED Single Head          | 4110150             | Slim Series XL 150w LED Work Light  |
| 514104            | Galaxy Pro w/ Tripod                            | 411350           | Slim Series 50-Watt LED Dual Head            | 4110220             | Slim Series XL 220w LED Work Light  |
| 514101            | NightSearcher Galaxy 1000                       | 111505           | ProLight XLE Series LED Work Light*          | 4110300             | Slim Series XL 300w LED Work Light  |
| 514102            | NightSearcher Galaxy 2000                       | 515100           | ProLight™™ 6000 Head Only                    |                     |                                     |
| 514124            | ProLight 30W Folding Light                      | 515103           | ProLight™™ 6000 Single Head w/ 2-Step Tripod |                     |                                     |
| 514125            | ProLight 30W Folding Light w/ Tripod            | 515104           | ProLight™™ 6000 Twin Head w/ 2-Step Tripod   |                     |                                     |
| 516001            | ProLight™ 100 Rechargeable LED Work Light**     |                  |  |                     |                                     |
| 516002            | ProLight™ 100 Rechargeable LED Work Light Kit** |                  |  |                     |                                     |
| 516003            | ProLight™ 200 Rechargeable LED Work Light**     |                  |  |                     |                                     |
| 516004            | ProLight™ 200 Rechargeable LED Work Light Kit** |                  |  |                     |                                     |

\*Also fits on 311007

\*\*Also fits on 311006

## ProLight™ 35w & 55w LED Dusk-to-Dawn Lights



The ProLight™ 35w & 55w LED Dusk-to-Dawn lights are the energy efficient replacement for the 150w High Pressure Sodium Light. This is an easy, maintenance free solution to outdoor area lighting needs for commercial and agricultural applications, ideal for use outdoors to illuminate large areas of property. These LED lights only uses 35 watts of power to produce 3,850 lumens or 55 watts of power to produce 6,050 lumens. The removable photocell sensor feature automatically turns the light on at dusk and turns it off at dawn. IP65 weather rated and rugged cast aluminum construction will protect the light from the harshest of conditions.

- LED Lighting
- IP65 Rated
- Cast Aluminum Housing
- Removable Photocell Sensor
- Polycarbonate Lens
- Mounting Bracket



| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life  | Kelvins | Watts | Amp Draw | Linking Units | Voltage | Temp Rated | Tested | Weight   | IP Rating |
|-----------|--------|----------------|-----------|------------|---------|-------|----------|---------------|---------|------------|--------|----------|-----------|
| 111511    | 3,850  | 50 ft          | LED       | 50,000 hrs | 5,000   | 35    | 0.4      | N/A           | 120V    | -30°-120°F | cUL    | 4.75 lbs | 4.75 lbs  |
| 111512    | 6,050  | 70 ft          | LED       | 50,000 hrs | 5,000   | 55    | 0.6      | N/A           | 120V    | -30°-120°F | cUL    | 4.75 lbs | 4.75 lbs  |

**HANG-A-LIGHT**  
by ProBuilt | Professional Lighting, LLC

## Magnetic Hang-A-Light®

The Hang-A-Light® Magnetic Work Lights are cUL listed for use in wet locations which makes them ideal for tank washing, machine shops or any confined space. It is energy efficient; with a heavy duty earth magnet on the back allowing this light to be attached to metal surfaces or the light can be hung by the eye hooks on the back.



- 6" Heavy Duty Earth Magnet
- Eye Hooks for Hanging
- 5' Integrated Power Cord
- No Exposed Glass
- No Hot Surfaces



42w / 111984

| Model No. | Lumens | Lighting Range | Bulb Type   | Lamp Life  | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Weight | IP Rating | Cord Type |
|-----------|--------|----------------|-------------|------------|---------|-------|----------|---------|------------|--------|--------|-----------|-----------|
| 111084    | 6,400  | 30 ft          | Fluorescent | 20,000 hrs | 3,500   | 84    | .76      | 120V    | -5°-120°F  | cUL    | 10 lbs | 65        | 14/3 SJTW |
| 111085    | 6,000  | 30 ft          | LED         | 40,000 hrs | 5,000   | 60    | .54      | 120V    | -30°-120°F | cUL    | 10 lbs | 65        | 14/3 SJTW |



The ProLight™ Dock Light features a high powered 20 watt LED head, delivering 1,700 lumens and a 15° beam angle. It also features a durable 40" steel arm to provide superior rigidity and prevent sagging. Arms are hinged for easy extension and compact folding when not in use. With a 60ft lighting range, this dock light will be sure to light up even the longest trailer for efficient loading and unloading.

### 40" Dock Light



- LED Lighting
- Durable and Versatile
- 60 ft Beam
- No hot surfaces
- IP65 Rated
- Pure white light

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life  | Features  | Kelvins | Watts | Amp Draw | Voltage | Temp Rated | Tested | Cord Type | Weight    | Beam Angle | IP Rating |
|-----------|--------|----------------|-----------|------------|-----------|---------|-------|----------|---------|------------|--------|-----------|-----------|------------|-----------|
| 111510    | 1,700  | 60 ft          | LED       | 50,000 hrs | 40" Arm   | 5,000   | 20    | .18      | 120V    | -30°-120°F | cUL    | 18/3 SJTW | 11.25 lbs | 15°        | 65        |
| 111515    | 1,700  | 60 ft          | LED       | 50,000 hrs | Head Only | 5,000   | 20    | .18      | 120V    | -30°-120°F | cUL    | 18/3 SJTW | 5.5 lbs   | 15°        | 65        |

### 4 ft. LED Shop Light



The all new ProLight™ 4ft LED Shop Light provides energy-efficient task lighting for utility applications in workshops, garages, manufacturing shops and many more. With the removable power cord and integrated ports, this light allows you to link up to 10 units together off of one plug in. Quickly replace existing fixtures by using the included chain and "S" hooks. The integrated LED's are energy efficient and cost effective while still delivering 4,500 lumens and 42 watts of power.

- Covered & Protected LED Strips
- No hot surfaces
- Durable Aluminum Housing
- Pure white light
- Interlink up to 10 Units

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life  | Features              | Kelvins | Watts | Amp Draw | Voltage | Tested | Linking Units | Weight    | Beam Angle | IP Rating |
|-----------|--------|----------------|-----------|------------|-----------------------|---------|-------|----------|---------|--------|---------------|-----------|------------|-----------|
| 111513    | 4,500  | 15 ft          | LED       | 50,000 hrs | "S" Hooks for Hanging | 5,000   | 42    | .4       | 120V    | cUL    | 10 Max        | 11.25 lbs | 15°        | 65        |

Enjoy the right kind of lighting anywhere you need it with the ProLight™ LED Drop Light. This LED Light provides bright light wherever you need it, with a magnet on the back to attach to anything metal and a hook on the top that rotates a full 360 degrees, this lets you easily attach this versatile work light overhead to give you clear illumination for your next project. It also includes a 12-amp receptacle on the bottom for convenience when working with other corded products.

### LED Drop Light



- LED Lighting
- Polycarbonate Lens
- Durable ABS Housing
- Hook & Magnet
- 12 Amp Receptacle
- 6' Cord

| Model No. | Lumens | Lighting Range | Bulb Type | Lamp Life  | Features                        | Kelvins | Watts | Amp Draw | Voltage | Tested | Weight   | Beam Angle |
|-----------|--------|----------------|-----------|------------|---------------------------------|---------|-------|----------|---------|--------|----------|------------|
| 515001    | 1,200  | 17 ft          | LED       | 30,000 hrs | 12 Amp Receptacle Hook & Magnet | 5,000   | 12    | 0.1      | 120V    | ETL    | 1.49 lbs | 45°        |

Utility Lights

## ProLight™ LED Pen & Inspection Light



The ProLight™ Pen Light offers two modes in one; Pen Light and Inspection Light. The Pen Light offers 100 Lumens and the Inspection Light offers 80 Lumens by utilizing the tail switch. The ProLight™ Pen Light also offers a 360° rotating magnet for hands free placement on metal surfaces.

- IP54 Rated
- 2 Modes
- 360° Rotating Magnet
- 12 ct Counter Display



| Model No. | Lumens    | Lighting Range | Bulb Type | Battery Type | Run Time       | Recharge Time | Modes                   | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|-----------|----------------|-----------|--------------|----------------|---------------|-------------------------|--------------|--------------|-----------|
| 511603    | 100<br>80 | 65 ft<br>15 ft | LED       | 2x AAA       | 1.5 hr<br>2 hr | N/A           | 2:<br>Inspection<br>Pen | 5.5          | 2.4          | 54        |

## ProLight™ LED Pen Light Set



The ProLight™ Pen Light Set offers two great pen lights in one package. The larger of the two Pen Lights offer 130 Lumens and the smaller of the two offers 80 Lumens. The ProLight™ Pen Light Set offer tail switch on/off and 360° rotating pocket clips.

- IP54 Rated
- 2 Lights
- 360° Rotating Pocket Clips
- 12 ct Counter Display



| Model No. | Lumens    | Lighting Range | Bulb Type | Battery Type     | Run Time       | Recharge Time | Modes    | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|-----------|----------------|-----------|------------------|----------------|---------------|----------|--------------|--------------|-----------|
| 511604    | 130<br>80 | 65 ft<br>30 ft | LED       | 2x AAA<br>1x AAA | 2.5 hr<br>2 hr | N/A           | 2 Lights | 5.5<br>3.75  | 1.6<br>.08   | 54        |

## NightSearcher

### NightSearcher® PocketStar LED Inspection Light



The NightSearcher® PocketStar is a compact, pocket sized LED light, providing a powerful 150 Lumen flood light that is ideal for inspection work and general illumination. It has a durable ABS body with soft-touch rubber coating. The magnetic pocket clip allows the light to be attached to metal surfaces for hands free use and may be swivelled through 180 degrees to shine the light in the correct position.

- IP33 Rated
- Durable ABS Body
- 180° Rotating Magnet
- 12 ct Counter Display



| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time | Recharge Time | Modes            | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|----------|---------------|------------------|--------------|--------------|-----------|
| 514001    | 150    | 15 ft          | LED       | 3x AAA       | 4 hrs    | N/A           | 1:<br>Inspection | 6.2          | 1.9          | 33        |



## NightSearcher® Explorer 800



The NightSearcher® Explorer 800 delivers a bright 1,640 foot beam with 800 lumens of output. Don't let the pocket size fool you; this robust, ultra-light aluminum body is designed to meet IPX4 and features a USB Rechargeable 3.7V Li-ion battery.

- IPX4 Rated
- 3 Modes: High/Low/Strobe
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time                                 | Recharge Time | Modes                    | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|--|---------------|--------------------------|--------------|--------------|-----------|
| 514004    | 800    | 1,640 ft       | LED       | Rechargeable Li-Ion | 3 hrs High<br>28 hrs Low<br>7 hrs Strobe | 5 hrs         | 3:<br>High/Low<br>Strobe | 5.9"         | 1.6          | X4        |



## ProLight™ Cannon



The ProLight™ Cannon delivers a bright 1,476 foot beam with 800 lumens of output. This robust, lightweight aluminum body is designed to meet IPX3 and features a USB Rechargeable Li-ion battery.

- IPX3 Rated
- 800 Lumens
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time | Recharge Time | Features  | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|----------|---------------|---|--------------|--------------|-----------|
| T0800     | 800    | 1,476 ft       | HID Xenon | Rechargeable Li-Ion | 1 hr     | 5 hrs         | Wall Charger/<br>Car Charger/<br>Shoulder Strap/<br>Carrying Case | 9.5"         | 24           | X3        |

## ProLight™ Blaster



The ProLight™ Blaster delivers a bright 1,640 foot beam with 1,000 lumens of output. This robust, lightweight aluminum body is designed to meet IPX3 and features a USB Rechargeable Li-ion battery. This light also features an adjustable lantern mode.

- IPX3 Rated
- 2 Modes: Beam & Lantern
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time | Recharge Time | Modes                   | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|----------|---------------|-------------------------|--------------|--------------|-----------|
| T1000     | 1,000  | 1,640 ft       | HID Xenon | Rechargeable Li-Ion | 2 hrs    | 5 hrs         | 2:<br>Beam &<br>Lantern | 12"          | 40           | X3        |

## ProLight™ Dominator



The ProLight™ Dominator delivers a bright 3,116 foot beam with 2,600 lumens of output. This robust, lightweight aluminum body is designed to meet IPX3 and features a USB Rechargeable Li-ion battery.

- IPX3 Rated
- High Output Beam
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time    | Recharge Time | Features  | Length (In.) | Weight (Oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|-------------|---------------|---|--------------|--------------|-----------|
| T2600     | 2,600  | 3,116 ft       | HID Xenon | Rechargeable Li-Ion | 1 hr/40 Min | 5 hrs         | Wall Charger/<br>Car Charger/<br>Shoulder Strap/<br>Carrying Case | 18"          | 54.4         | X3        |

## ProLight™ Carbon Fiber 1

The ProLight™ Carbon Fiber Series 1 has a durable aluminum body with a carbon fiber handle. This unit also has an adjustable beam for flood or spot, a tail switch for convenient on and off, a pocket clip as well as a magnet on the tail for hands free use.



- IP44 Rated
- Adjustable Beam
- Tail Magnet

| Model No | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time | Features  | Length (in.) | Weight (oz.) | IP Rating |
|----------|--------|----------------|-----------|--------------|----------|---|--------------|--------------|-----------|
| CF001    | 275    | Adjustable     | LED       | 3x AAA       | 2 hrs    | Adjustable Beam<br>Carbon Fiber Handle<br>Tail Switch<br>Magnet | 4.5"         | 4.8          | 44        |

## ProLight™ Carbon Fiber 2

The ProLight™ Carbon Fiber Series 2 has a durable aluminum body with a carbon fiber handle. This unit also has an adjustable beam for flood or spot, a tail switch for convenient on and off and a pocket clip.



- IP44 Rated
- Adjustable Beam
- Tail Switch

| Model No | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time | Features  | Length (in.) | Weight (oz.) | IP Rating |
|----------|--------|----------------|-----------|--------------|----------|---|--------------|--------------|-----------|
| CF002    | 480    | Adjustable     | LED       | 4x AA        | 3 hrs    | Adjustable Beam<br>Carbon Fiber Handle<br>Tail Switch | 10"          | 14.4         | 44        |

## ProLight™ Carbon Fiber 3

The ProLight™ Carbon Fiber Series 3 has a durable aluminum body with a carbon fiber handle. This unit also has an adjustable beam for flood or spot, a tail switch for convenient on and off and a pocket clip.



- IP44 Rated
- Adjustable Beam
- Tail Switch

| Model No | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time | Features  | Length (in.) | Weight (oz.) | IP Rating |
|----------|--------|----------------|-----------|--------------|----------|---|--------------|--------------|-----------|
| CF003    | 310    | Adjustable     | LED       | 2x D         | 3 hrs    | Adjustable Beam<br>Carbon Fiber Handle<br>Tail Switch | 10.25"       | 23.2         | 44        |

## ProLight™ Carbon Fiber 4

The ProLight™ Carbon Fiber Series 4 has a durable aluminum body with a carbon fiber handle. This unit also has an adjustable beam for flood or spot, a tail switch for convenient on and off and a pocket clip.



- IP44 Rated
- Adjustable Beam
- Tail Switch

| Model No | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time | Features  | Length (in.) | Weight (oz.) | IP Rating |
|----------|--------|----------------|-----------|--------------|----------|---|--------------|--------------|-----------|
| CF004    | 500    | Adjustable     | LED       | 3x D         | 7 hrs    | Adjustable Beam<br>Carbon Fiber Handle<br>Tail Switch | 12.6"        | 32           | 44        |



## NightSearcher® Explorer X1



The Explorer-X1 delivers a bright 328 foot beam, and has a powerful 120 lumens output. This pocket sized, robust and ultra light aluminum body flashlight also features advanced Cree XB-H T4 LED's and three light modes to suit your needs with an 8 hour running time on the low setting.

- IPX4 Rated
- 3 Modes
- Durable and Impact Resistant

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time                               | Features                     | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|--|------------------------------|--------------|--------------|-----------|
| 514002    | 120    | 328 ft.        | LED       | 1x AA        | 2 hr high<br>8 hr low<br>1.5 hr strobe | 3 Modes: High/<br>Low/Strobe | 4.4"         | 2.7          | X4        |

## NightSearcher® Explorer X2



The Explorer-X2 delivers a bright 820 foot beam, and has a powerful 280 lumens output. This pocket sized, robust and ultra light aluminum body also features advanced Cree XB-H T4 LED's and three light modes to suit your needs with a 25 hour running time on the low setting.

- IPX8 Rated
- 3 Modes
- Durable and Impact Resistant

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time                                  | Features                     | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|---|------------------------------|--------------|--------------|-----------|
| 514003    | 280    | 820 ft.        | LED       | 3x AAA       | 2.5 hr high<br>25 hr low<br>2.5 hr strobe | 3 Modes: High/<br>Low/Strobe | 4.5"         | 4.3          | X8        |



## ProLight™ ProTorch 601S



The ProLight™ ProTorch 601S features an adjustable flood to spot beam up to 60 feet with a powerful 250 lumen output. This durable aluminum body light also features three light modes to suit your needs with a 6 hour running time on the low setting.

- IP54 Rated
- Adjustable Beam
- Tail Switch

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time                                 | Features                     | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|--|------------------------------|--------------|--------------|-----------|
| 511601    | 250    | 60 ft          | LED       | 3x AAA       | 2.5 hr high<br>6 hr low<br>1.5 hr strobe | 3 Modes: High/<br>Low/Strobe | 6"           | 5.1          | 54        |

## ProLight™ ProTorch 602T



The ProLight™ ProTorch 602T features an adjustable flood to spot beam up to 60 feet with a powerful 250 lumen output. This durable aluminum body light also features three light modes to suit your needs with a 10 hour running time on the low setting.

- IP54 Rated
- Adjustable Beam
- Tail Switch

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time                              | Features                     | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|---------------------------------------|------------------------------|--------------|--------------|-----------|
| 511602    | 250    | 60 ft          | LED       | 6x AAA       | 5 hr high<br>10 hr low<br>3 hr strobe | 3 Modes: High/<br>Low/Strobe | 7.625"       | 8.2          | 54        |

## NightSearcher® Trio-550 Searchlight



The NightSearcher® TRIO-550 has a long range beam of up to 1,968 feet. The TRIO 550 is ideal for Patrolling, Security Guards, Search & Rescue, and with robust construction it's durable enough for all applications. The TRIO 550 features an emergency function to automatically illuminate in the event of a power cut. It can be mounted on walls or in vehicles using the bracket supplied.

- IP54 Rated
- 3 Modes
- Emergency Mode

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time                              | Features                   | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|---------------------------------------|----------------------------|--------------|--------------|-----------|
| 511600    | 550    | 1,968 ft.      | LED       | Rechargeable Li-Ion | 3 hr high<br>7 hr low<br>15 hr strobe | 3 Modes: High/Low/Flashing | 7.6"         | 22           | 54        |

## NightSearcher® Panther XM-L Searchlight



The NightSearcher® PANTHER XM-L is now upgraded with the latest LED technology increasing the running time to 6hrs on full and 3hrs on half power. The unique deep dish reflector enables maximum distance to lumen ratio achieving a 4,921 foot beam from only 1,500 lumens; weighing under 19 ounces it is our lightest in the range.

- IP54 Rated
- 2 Modes
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time              | Features          | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|-----------------------|-------------------|--------------|--------------|-----------|
| 511301    | 1,500  | 4,921 ft.      | LED       | Rechargeable Li-Ion | 3 hr high<br>6 hr low | 2 Modes: High/Low | 10.3"        | 19           | 54        |

## NightSearcher® HT180 HeadLamp



The NightSearcher® HT180 is a head torch boasting 180 lumens of light output, delivering a 328 foot beam. This headlamp also features proximity distance dimming for close up work, three light modes: spot, wide beam and distance dimming as well as an adjustable non-slip head strap.

- IPX4 Rated
- 3 Modes
- Distance Dimming

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time                | Features                            | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|-------------------------|-------------------------------------|--------------|--------------|-----------|
| 514010    | 180/35 | 328 ft.        | LED       | 3x AAA       | 3 hr high<br>130 hr low | 3 Modes: Spot/Wide/Distance Dimming | 2.44         | 3.5          | X4        |

## NightSearcher® HT340R HeadLamp



The NightSearcher® HT340R is a rechargeable Li-ion head torch boasting 340 lumens of light output, delivering a 656 foot beam. This headlamp also features proximity distance dimming for close up work, three light modes: spot, wide beam and distance dimming as well as an adjustable non-slip head strap and USB cable for charging.

- IP66 Rated
- 3 Modes
- Rechargeable
- Distance Dimming

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type        | Run Time                  | Features                            | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|---------------------|---------------------------|-------------------------------------|--------------|--------------|-----------|
| 511924    | 340/60 | 656 ft.        | LED       | Rechargeable Li-Ion | 1.5 hr high<br>130 hr low | 3 Modes: Spot/Wide/Distance Dimming | 2.44"        | 3.5          | 66        |



### NightSearcher® Intrinsically Safe Torch EX125



The NightSearcher® EX125 Intrinsically Safe LED flashlight for use in Zone 0 hazardous areas has a beam of up to 472 feet, high powered LED - CREE XP-G2. This unit is waterproof up to 1m, features a switch push button on tail, aluminum heat sink enhancing LED efficiency and can sustain drops up to 1m.

- IP67 Rated
- Intrinsically Safe
- 2 Modes

| Model No. | Lumens | Lighting Range      | Bulb Type | Battery Type | Run Time                  | Features                                   | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|---------------------|-----------|--------------|---------------------------|--|--------------|--------------|-----------|
| 514007    | 125/55 | 472 ft./<br>295 ft. | LED       | 3x C         | 42.5 hr high<br>80 hr low | 2 Modes:<br>High/Low<br>Intrinsically Safe | 8.85         | 6.7          | 67        |

### NightSearcher® Intrinsically Safe Torch EX160



The NightSearcher® EX160 Intrinsically Safe LED flashlight for use in Zone 0 hazardous areas has a beam of up to 393 feet, high powered LED - CREE XP-G2. This unit is waterproof up to 1m, features a switch push button on tail, aluminum heat sink enhancing LED efficiency and can sustain drops up to 1m.

- IP67 Rated
- Intrinsically Safe
- 2 Modes

| Model No. | Lumens | Lighting Range      | Bulb Type | Battery Type | Run Time               | Features                                   | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|---------------------|-----------|--------------|------------------------|--|--------------|--------------|-----------|
| 514008    | 160/65 | 393 ft./<br>213 ft. | LED       | 4x AA        | 6 hr high<br>13 hr low | 2 Modes:<br>High/Low<br>Intrinsically Safe | 6.7"         | 4.9          | 67        |

### NightSearcher® Intrinsically Safe Right Angle Torch EX270



The NightSearcher® EX270 Right Angle Intrinsically Safe LED flashlight for use in Zone 0 has a beam of up to 820 feet featuring 270 Lumens of output. This light also has 2 Light modes; high and low and a running time of 13 hrs on low. It also has an air free heat sink design to enhance LED heat dissipation and a gas pressure release valve.

- IP54 Rated
- Intrinsically Safe
- 2 Modes

| Model No. | Lumens  | Lighting Range      | Bulb Type | Battery Type | Run Time                 | Features                                   | Length (in.) | Weight (oz.) | IP Rating |
|-----------|---------|---------------------|-----------|--------------|--------------------------|--|--------------|--------------|-----------|
| 514009    | 270/135 | 820 ft./<br>590 ft. | LED       | 4x AA        | 6.5 hr high<br>13 hr low | 2 Modes:<br>High/Low<br>Intrinsically Safe | 7.2"         | 8.8          | 54        |

### NightSearcher® Intrinsically Safe HeadLamp EXHT180



The NightSearcher® EXHT180 Intrinsically safe LED Headlamp for use in Zone 0 hazardous areas features 200 lumens of light output on full and 100 on half. This durable impact resistant headlamp also features an adjustable headband to fit users head or helmet, a 90° Rotational head, waterproof up to 1m and powered by 3x AAA batteries.

- IP67 Rated
- Intrinsically Safe
- 2 Modes

| Model No. | Lumens  | Lighting Range      | Bulb Type | Battery Type | Run Time                  | Features                                   | Length (in.) | Weight (oz.) | IP Rating |
|-----------|---------|---------------------|-----------|--------------|---------------------------|--|--------------|--------------|-----------|
| 514012    | 200/100 | 328 ft./<br>246 ft. | LED       | 3x AAA       | 2.5 hr high<br>4.5 hr low | 2 Modes:<br>High/Low<br>Intrinsically Safe | 3.14"        | 5            | 67        |

## Defender® Rechargeable LED Hand Lamp



The Defender® Rechargeable LED Hand Lamp is a tough, strong and durable portable lighting solution that delivers a bright 64 lumens of light. It also features a detachable base, easy-grip handle and pivoting hook for multiple working positions as well as a tough polycarbonate lens and ABS body that provide strong impact protection. As well as 26 solid state high output, low energy LEDs to provide a wide bright light spread.

- IP44 Rated
- 2 Modes
- Rechargeable

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time              | Features             | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|-----------------------|----------------------|--------------|--------------|-----------|
| E712810   | 64     | 8 ft.          | LED       | Rechargeable | 3 hr high<br>6 hr low | 2 Modes:<br>High/Low | 16.5"        | 8            | 44        |

## Defender® Mini Mobi



The Defender® LED Mini Mobi Inspection light is a durable, battery powered lighting solution. It includes an integrated floor stand, hanging hook and magnet for multiple working positions. It has a durable, tough ABS body, rubber over mould, and shatterproof lens that withstands knocks and drops with 20 low energy ultra bright LEDs to provide a wide spread of clean, white light.

| Model No. | Lumens | Lighting Range | Bulb Type | Battery Type | Run Time              | Features             | Length (in.) | Weight (oz.) | IP Rating |
|-----------|--------|----------------|-----------|--------------|-----------------------|----------------------|--------------|--------------|-----------|
| E712848   | 55     | 8 ft.          | LED       | 3x AA        | 3 hr high<br>8 hr low | 2 Modes:<br>High/Low | 5.75"        | 4            | 44        |

## NightSearcher® Pulsars



The NightSearcher® PULSAR is a multi-mode, rechargeable LED warning light; designed for traffic control, signaling, hazard awareness, zone demarcations and vehicle safety. Ideal for professional applications, including the Police, Fire and Highway Services. These small but robust units are manufactured in shock resistant plastic housing, are waterproof (up to 10 meters) and virtually indestructible (withstanding most vehicle weights if crushed). Built in magnets allow attachment to vehicles or any metal surfaces.

| Model No. | Model                      | Lighting Range         | Bulb Type | Battery Type | Run Time              | Features | Temp Rated    | Weight (oz.) | IP Rating |
|-----------|----------------------------|------------------------|-----------|--------------|-----------------------|----------|---------------|--------------|-----------|
| 511701    | Set of 5 (Mix & Match)     | Visible up to 3,000 ft | LED       | Rechargeable | Reference Chart Below | 10 Modes | -40°F - 140°F | 7            | 67        |
| 511702    | Yellow Kit (set of 5)      |                        |           |              |                       |          |               |              |           |
| 511703    | Blue Kit (set of 5)        |                        |           |              |                       |          |               |              |           |
| 511705    | Red Kit (set of 5)         |                        |           |              |                       |          |               |              |           |
| 511706    | Yellow Single (w/ Charger) |                        |           |              |                       |          |               |              |           |
| 511707    | Blue Single (w/ Charger)   |                        |           |              |                       |          |               |              |           |
| 511709    | Red Single (w/ Charger)    |                        |           |              |                       |          |               |              |           |

| Mode   | Run Time | Mode               | Run Time |
|--|----------|--------------------|----------|
| Recharge Time: 12-14 hours (all 5 units) 2-6 hours (1-3 units) |          |                    |          |
| Rotate   | 8 hrs    | Quad Flash         | 8 hrs    |
| Single Blink   | 25 hrs   | Alternating Blinks | 8 hrs    |
| SOS Rescue   | 12 hrs   | Steady ON: High    | 7 hrs    |
| Steady ON: Low   | 20 hrs   | 2 LED Flashlight   | 25 hrs   |
| 4 LED Flashlight   | 18 hrs   | White Torch Mode   | 20 hrs   |



- Available in Yellow, Blue or Red
- Can withstand 10 tons of weight
- Designed with integrated magnets
- Car and wall chargers included



# Handheld Lighting Specifications Chart

| Model No.                 | Lumens     | Lighting Range | Bulb Type    | Battery Type     | Run Time                                     | Recharge Time | Modes    | Length (in.)  | Weight (oz.) | IP Rating |
|---------------------------|------------|----------------|--------------|------------------|--|---------------|----------|---------------|--------------|-----------|
| <b>PenLights</b>          |            |                |              |                  |  |               |          |               |              |           |
| 511603                    | 100<br>80  | 65 ft<br>15 ft | LED          | 2x AAA           | 1.5 hrs<br>2 hrs                             | N/A           | 2        | 5.5"          | 2.4          | 54        |
| 511604                    | 130<br>80  | 65 ft<br>30 ft | LED          | 2x AAA<br>1x AAA | 2.5 hrs<br>2 hrs                             | N/A           | 2 lights | 5.5"<br>3.75" | 1.6<br>.08   | 54        |
| 514001                    | 150        | 15 ft          | LED          | 3x AAA           | 4 hrs  | N/A           | 1        | 6.2           | 1.9          | 33        |
| <b>Rechargeable</b>       |            |                |              |                  |  |               |          |               |              |           |
| 514004                    | 800        | 1,640 ft       | LED          | Rechargeable     | 3 hrs high<br>28 hrs low<br>7 hrs Strobe     | 5 hrs         | 3        | 5.9"          | 1.6          | X4        |
| T0800                     | 800        | 1,476 ft       | HID<br>Xenon | Rechargeable     | 1 hr   | 5 hrs         | 1        | 9.5"          | 24           | X3        |
| T1000                     | 1,000      | 1,640 ft       | HID<br>Xenon | Rechargeable     | 2 hrs  | 5 hrs         | 2        | 12"           | 40           | X3        |
| T2600                     | 2,600      | 3,116 ft       | HID<br>Xenon | Rechargeable     | 1 hr/40 min                                  | 5 hrs         | 1        | 18"           | 54.4         | X3        |
| <b>Non-Rechargeable</b>   |            |                |              |                  |  |               |          |               |              |           |
| CF001                     | 275        | Adjustable     | LED          | 3x AAA           | 2 hrs  | N/A           | 2        | 4.5"          | 4.8          | 44        |
| CF002                     | 480        | Adjustable     | LED          | 4x AA            | 3 hrs  | N/A           | 2        | 10"           | 14.4         | 44        |
| CF003                     | 310        | Adjustable     | LED          | 2x D             | 3 hrs  | N/A           | 2        | 10.25"        | 23.2         | 44        |
| CF004                     | 500        | Adjustable     | LED          | 3x D             | 7 hrs  | N/A           | 2        | 12.6"         | 32           | 44        |
| 514002                    | 120        | 328 ft         | LED          | 1x AA            | 2 hrs high<br>8 hrs low<br>1.5 hrs strobe    | N/A           | 3        | 4.4"          | 2.7          | X4        |
| 514003                    | 280        | 820 ft         | LED          | 3x AAA           | 2.5 hrs high<br>25 hrs low<br>2.5 hrs strobe | N/A           | 3        | 4.5"          | 4.3          | X8        |
| 511601                    | 250        | 60 ft          | LED          | 3x AAA           | 2.5 hrs high<br>6 hrs low<br>1.5 hrs strobe  | N/A           | 3        | 6"            | 5.1          | 54        |
| 511602                    | 250        | 60 ft          | LED          | 6x AAA           | 5 hrs high<br>10 hrs low<br>3 hrs strobe     | N/A           | 3        | 7.625"        | 8.2          | 54        |
| <b>Searchlights</b>       |            |                |              |                  |  |               |          |               |              |           |
| 511600                    | 550        | 1,968 ft       | LED          | Rechargeable     | 3 hrs high<br>7 hrs low<br>15 hrs strobe     | 12 hrs        | 3        | 7.6"          | 22           | 54        |
| 511301                    | 1,500      | 4,921 ft       | LED          | Rechargeable     | 3 hrs high<br>6 hrs low                      | 8 hrs         | 2        | 10.3"         | 19           | 54        |
| <b>Headlamps</b>          |            |                |              |                  |  |               |          |               |              |           |
| 514010                    | 180<br>35  | 328 ft         | LED          | 3x AAA           | 3 hrs high<br>130 hrs low                    | N/A           | 3        | 2.44"         | 3.5          | X4        |
| 511924                    | 340<br>60  | 656 ft         | LED          | Rechargeable     | 1.5 hrs high<br>130 hrs low                  | 5 hrs         | 3        | 2.44"         | 3.5          | 66        |
| <b>Intrinsically Safe</b> |            |                |              |                  |  |               |          |               |              |           |
| 514007                    | 125<br>55  | 472 ft         | LED          | 3x C             | 42.5 hrs high<br>80 hrs low                  | N/A           | 2        | 8.85"         | 6.7          | 67        |
| 514008                    | 160<br>65  | 393 ft         | LED          | 4x AA            | 6 hrs high<br>13 hr low                      | N/A           | 2        | 6.7"          | 4.9          | 67        |
| 514009                    | 270<br>135 | 820 ft         | LED          | 4x AA            | 6.5 hrs high<br>13 hrs low                   | N/A           | 2        | 7.2"          | 8.8          | 54        |
| 514012                    | 200<br>100 | 328 ft         | LED          | 3x AAA           | 2.5 hrs high<br>4.5 hrs low                  | N/A           | 2        | 3.14"         | 5            | 67        |
| <b>Handlamps</b>          |            |                |              |                  |  |               |          |               |              |           |
| E712810                   | 64         | 8 ft           | LED          | Rechargeable     | 3 hrs high                                   | 5 hrs         | 2        | 16.5"         | 8            | 44        |
| E712848                   | 55         | 8 ft           | LED          | 3x AA            | 3 hrs high<br>8 hrs low                      | N/A           | 2        | 5.75"         | 4            | 44        |

# Hang-A-Light® Fixture Spacing Guidelines

| Model/Ceiling Height | 8'  | 12' | 16' | 20' | 24' | 28' | 32' | 36' | 40' |
|----------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 111060LED            | 25' | 25' | 18' | 18' | 16' | 16' |     |     |     |
| 111105F              | 22' | 22' | 18' | 18' | 18' | 16' | 16' |     |     |
| 111080LED            | 25' | 25' | 25' | 25' | 22' | 22' | 22' | 18' | 18' |
| 111080ECO            |     | 25' | 25' | 22' | 22' | 22' | 22' | 22' | 18' |
| 1110100LED           |     | 25' | 25' | 25' | 25' | 22' | 22' | 22' | 22' |
| 1110150LED           |     |     | 25' | 25' | 25' | 25' | 22' | 22' | 22' |
| 111200LED            |     |     | 25' | 25' | 25' | 25' | 22' | 22' | 22' |
| 111400PS             |     |     |     | 38' | 38' | 38' | 38' | 32' | 32' |

\*Approximate fixture spacing (ft.) shown to achieve 5 foot-candles (FC) at ground level

\*\*Calculations based on 100' x 100' area, actual fixture spacing may vary depending on many factors


| Model No.         | Height    | # of Fixtures | Watts / Sq. Ft. | Coverage / Fixture    | Spacing Approx. |
|-------------------|-----------|---------------|-----------------|-----------------------|-----------------|
| 111060LED - 60w   | 8' - 12'  | 12            | .07             | 833 ft <sup>2</sup>   | 25'             |
|                   | 13' - 26' | 16            | .09             | 625 ft <sup>2</sup>   | 18'             |
|                   | 26' - 30' | 20            | .12             | 500 ft <sup>2</sup>   | 16'             |
| 111080LED - 80w   | 12' - 22' | 9             | .07             | 1,111 ft <sup>2</sup> | 25'             |
|                   | 13' - 25' | 12            | .10             | 833 ft <sup>2</sup>   | 22'             |
|                   | 36' - 40' | 16            | .13             | 625 ft <sup>2</sup>   | 18'             |
| 111080ECO - 80w   | 10' - 19' | 9             | .07             | 1,111 ft <sup>2</sup> | 25'             |
|                   | 20' - 39' | 12            | .10             | 833 ft <sup>2</sup>   | 22'             |
|                   | 40' - 48' | 16            | 0.12            | 625 ft <sup>2</sup>   | 18'             |
| 1110100LED - 100w | 12' - 30' | 9             | .08             | 1,111 ft <sup>2</sup> | 25'             |
|                   | 31' - 42' | 12            | .12             | 833 ft <sup>2</sup>   | 22'             |
|                   | 43' - 50' | 15            | .15             | 667 ft <sup>2</sup>   | 20'             |
| 1110150LED - 150w | 14' - 31' | 6             | .09             | 1,667 ft <sup>2</sup> | 25'             |
|                   | 32' - 49' | 9             | .14             | 1,111 ft <sup>2</sup> | 22'             |
|                   | 50+'      | 12            | .18             | 833 ft <sup>2</sup>   | 20'             |
| 111105F - 105w    | 8' - 12'  | 12            | .12             | 833 ft <sup>2</sup>   | 22'             |
|                   | 13' - 28' | 16            | .17             | 625 ft <sup>2</sup>   | 18'             |
|                   | 29' - 40' | 20            | .21             | 500 ft <sup>2</sup>   | 16'             |
| 111200LED - 150w  | 14' - 28' | 4             | .07             | 2,500 ft <sup>2</sup> | 25'             |
|                   | 29' - 40' | 9             | .12             | 1,111 ft <sup>2</sup> | 22'             |
|                   | 50+'      | 12            | .14             | 833 ft <sup>2</sup>   | 18'             |
| 111400PS - 400w   | 10' - 40' | 4             | .17             | 2,500 ft <sup>2</sup> | 38'             |
|                   | 41' - 80' | 6             | .25             | 1,667 ft <sup>2</sup> | 32'             |
|                   | 80+'      | 9             | .38             | 1,111 ft <sup>2</sup> | 25'             |

\*Approximate fixture spacing (ft.) shown to achieve 5 foot-candles (FC) at ground level

\*\*Calculations based on 100' x 100' area, actual fixture spacing may vary depending on many factors

\*\*\*Reflectance 50/50/20

# ProBuilt can handle your lighting layout needs!



*\*Layout is based on 100w LED Hang-A-Light at 18' ceiling height in a 100' x 100' room*

## Need a custom temporary lighting layout?

ProBuilt Professional Lighting has the expertise and capability to develop customized temporary lighting layouts for qualified bids and projects. Lighting layouts can take into consideration the work area dimensions, ceiling height and target illumination levels. The ProBuilt Hang-A-Light category can then be modeled to determine the most cost effective and energy-efficient lighting layout possible for a customized lighting solution.

Custom layouts can be critical to end users in providing support with:

- Selecting the most effective fixtures based on job site conditions
- Creating a budget for temporary lighting
- Fixture installation and spacing
- Accurately calculating and optimizing energy usage
- Insuring there will be adequate illumination levels in all work areas
- Specifying ProBuilt fixtures for future projects

For support with lighting needs, please contact us toll free at 877-707-0800.



## IP First number - Protection against solid objects

|   |   |
|---|---|
| 0 | No Special Protection   |
| 1 | Protected against solid objects up to 50 mm, e.g. accidental touch by persons hands |
| 2 | Protected against solid objects up to 12 mm, e.g. persons fingers                   |
| 3 | Protected against solid objects over 2.5 mm (tools and wires)                       |
| 4 | Protected against solid objects over 1 mm (tools, wires, and small wires)           |
| 5 | Protected against dust limited ingress (no harmful deposit)                         |
| 6 | Totally protected against dust  |

## IP Second number - Protection against liquids

|   |   |
|---|---|
| 0 | No protection   |
| 1 | Protection against vertically falling drops of water e.g. condensation                              |
| 2 | Protection against direct sprays of water up to 15° from the vertical.                              |
| 3 | Protected against direct sprays of water up to 60° from the vertical                                |
| 4 | Protection against water sprayed from all directions - limited ingress permitted                    |
| 5 | Protected against low pressure jets of water from all directions - limited ingress                  |
| 6 | Protected against temporary flooding of water, e.g. for use on ship decks-limited ingress permitted |
| 7 | Protected against the effect of immersion between 15cm and 1m                                       |
| 8 | Protects against long periods of immersion under pressure   |

### What does the IP Rating Mean?

The IP Code (or Ingress Protection Rating) classifies and rates the degrees of protection provided against the intrusion of solid objects, dust, accidental contact, and water in mechanical casings and with electrical enclosures.

### What is a Lumen?


A LUMEN is a unit of measurement of light that measures the amount of brightness that comes from a light source. A LUMEN is equal to one foot-candle falling on one square foot of area. A foot-candle is how bright the light is one foot away from the source.

### What does "Intrinsically Safe" mean?

The term "Intrinsically Safe" (I.S.) is frequently used to describe any product destined for an explosive area. In reality, I.S. is a protection concept based around limiting the available electrical energy to nonincendive levels so that sparks cannot occur from short circuit or failures which could cause an explosive atmosphere to ignite.

## Kelvin "Color Temperature Chart"

Color Temperature and LED efficiency have a direct relationship that need to be balanced to produce a quality work light. Color Temperature is measured in degrees Kelvin (K) and typically ranges from 2,500 to 6,000 or higher. As color temperature increases the human perception of light moves from a yellow/orange appearance (on the low end) to a blue/white appearance (on the high end). As color temperature increases the efficiency of a light source also typically increases. However, at high color temperatures the light can become stark or harsh, which can be harder to work with/around. Color Temperatures between 4000K and 5500K produce a neutral light which is most similar to natural daylight which is easier to work under and to be able to distinguish colors. Above 5500K you begin to get into the harsh white light of mid-day sun and blue tints begin to be seen while blues and greens will begin to look the same. The top LED bulb manufacturers like Cree, Bridgelux & Epistar balance color temperature and efficiency to produce 80-110 lumens/watt while having a color temperature of 4500K-5000K. This is why ProBuilt Lighting produces work lights with these types of LED's.



## The LED Energy Savings Advantage!

Making the initial investment into LED products may seem expensive, but there are many benefits that need to be taken into consideration. The durability, safety features and energy savings of LED products far out weigh the expense. Do the comparison!

| Part #     | Description            | Total Wattage | Comparison Light  | Hours of Use Per Day | Annual Savings* | Payback Period |
|------------|------------------------|---------------|-------------------|----------------------|-----------------|----------------|
| XLE Series | 50w Series             | 50            | 500w Halogen      | 12                   | \$277.00        | 11 Months      |
| 11136LED   | LED Wobblelight        | 80            | 400w Metal Halide | 24                   | \$440.00        | 4 Months       |
| 411015     | 15w LED Floodlight     | 15            | 250w Halogen      | 12                   | \$154.00        | 5 Months       |
| 411030     | 30w LED Floodlight     | 30            | 250w Halogen      | 12                   | \$144.00        | 8 Months       |
| 411050     | 50w LED Floodlight     | 50            | 500w Halogen      | 12                   | \$296.00        | 7 Months       |
| 111060LED  | 60w LED Hang-A-Light   | 60            | 175w Metal Halide | 24                   | \$177.00        | 2 Months       |
| 111080ECO  | 80w LED Hang-A-Light   | 80            | 250w Metal Halide | 24                   | \$229.00        | 4 Months       |
| 1110100LED | 100w LED Hang-A-Light  | 100           | 400w Metal Halide | 12                   | \$269.00        | 4 Months       |
| 111100     | 100ft LED String Light | 140           | 100w Incandescent | 24                   | \$264.00        | 2 Month        |

\* Based on \$0.15 per kwh  
LED Savings Calculator (<https://www.probuillighting.com/led-bulb-saving-calculator/>)



# ProBuilt | Professional Lighting, LLC

Designed for the Pros



877-707-0800



847-577-3875



[www.probuiltilighting.com](http://www.probuiltilighting.com)



[Instagram.com/ProBuiltLighting](https://www.instagram.com/ProBuiltLighting)



[Facebook.com/ProBuiltProfessionalLighting](https://www.facebook.com/ProBuiltProfessionalLighting)



[Twitter.com/ProBuiltLights](https://twitter.com/ProBuiltLights)



ProBuilt Professional Lighting