
4AA ProPolymer® Lux DIV 1/DIV 2 Alkaline Battery-Powered Flashlight





Case Material: Engineering polymer resin that is virtually indestructible, shock resistant, non-conductive and light weight.

Dimensions: Length: 7.00 in. (17.78 cm) Body thickness: 0.97 in. (2.46 cm) Width: 1.35 in. (3.43 cm) Facecap diameter: 1.69 in. (4.29 cm) Body Diameter: 1.48 in. (3.76 cm)

Weight: 7.6 oz (216 grams) with batteries

ens: Unbreakable polycarbonate lens with scratch resistant coating

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime

On/Off: Push button tail switch provides one handed momentary or constant operation

Battery: Four "AA" alkaline batteries (included)

Features: IP67 rated design; waterproof to 1 meter for 30 minutes.

1 meter impact resistance tested. Non-conductive; Corrosion proof

Deep parabolic reflector produces long range brilliance and smooth uniform beam pattern.

Optimized electronics provides maximum light output throughout battery life.

Approvals: Most models meet applicable European Community Directives.

DIVISION 1:

UL Listed Class I, Division 1, Groups C & D; Class I, Division 2, Groups A,B,C,D;

Class II, Division 1, Groups F & G; Class III; Exia; Temperature Code T4

MSHA: Permissible Flashlight; Approval No.20-A060002-0; Tested for use in Methane-Air mixtures only

DIVISION 2:

UL Listed Class I, Division 2, Groups A, B, C & D;

Class II, Division 2, Groups F & G; Class III; Temperature Code T3C

ATEX Model: Zone 1: II 2GD EEx ib IIB T4 IP65 (T67C) - SNCH 04 ATEX 3639

Warranty:

Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

^{**} See product for specific ratings.

Item		UPC	Part #	
4AA Lux with alkaline batteries. Div 2	Yellow	080926-68244-3	68244	
4AA Lux with alkaline batteries. Div 2	Black	080926-68344-0	68344	
4AA Lux with alkaline batteries. Div 1	Yellow	080926-68602-1	68602	
4AA Lux with alkaline batteries. Div 1	Black	080926-68702-8	68702	
See back for accessories				







Adheres to side of hard hat



Poly Mount Kit - universal mounting via MSA V-Gard slot or self-adhesive mount

Includes straps for mounting the 4AA ProPolymax/3AA ProPolymer HAZ-LO, 2AA ProPolymer® Series or the PolyTac® LED Series

Clips onto hard hats

Item		UPC	Part #
Safety Wand	Yellow	080926-75904-6	75904
Safety Wand	Red	080926-75903-9	75903
Safety Wand	Blue	080926-75902-2	75902
Safety Wand	White	080926-75908-4	75908
Safety Wand	Glow-in-the-dark	080926-75913-8	75913
4AA helmet mount		080926-68269-6	68269
Rubber Helmet Strap		080926-99075-3	99075
Poly Mount		080926-68089-0	68089





