

# TRIM<sup>®</sup> TC 239

Paintable Antifoam/Defoamer

### **GENERAL DESCRIPTION**

TRIM<sup>®</sup> TC 239 is a paintable, platable additive used to control foam in metalworking fluids and parts washing systems.

### **APPLICATION GUIDELINES**

- Start by adding 2 ounces of TC 239 per 100 gallons of solution to lower foam. You may find that using less than this will be effective in your system.
- Shake or stir well before adding. For best results, premix TC 239 with working solution until it is water-thin. This mixture should be added just up-stream from the foam.
- The maximum amount of TC 239 in the system should not exceed 16 ounces per one hundred gallons of metalworking fluid. Using too much TC 239 can cause foam and/or form a residue on the machine, parts, or tools.
- Spraying premixed TC 239 directly onto the foam will also knock it down quickly.
- Do not freeze or store above 115°F.

### **HEALTH & SAFETY**

See the most recent SDS at 2trim.us/s/?i=1087-en-US-US.

## TECHNICAL ASSISTANCE

- For additional product applications information including performance optimization, please contact your Master Chemical Authorized Distributor at <u>2trim.us/distributors.php</u>, your District Sales Manager, the Tech Line at 1-800-537-3365, or visit our web site at <u>www.masterchemical.com</u>.
- Packaging: North America 2-quart measuring jug, 1-gallon jug, 5-gallon pail, and 54-gallon drum

### PHYSICAL PROPERTIES (TYPICAL DATA)

Form ..... Liquid Color ..... White

The information herein is given in good faith and believed current as of the date of this Data & Information sheet and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Chemical Corporation for further information. For the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the date of this Data & Information sheet and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Chemical Corporation for further information. For the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document, please go to this URL: <a href="https://www.example.com">https://www.example.com</a> the most recent version of this document.

TRIM<sup>®</sup> is a registered trademark of Master Chemical Corporation

© 2001-2015 Master Chemical Corporation • Revised October 8, 2015

Tel: 419-874-7902 Email: info@masterchemical.com Web: www.trimfluids.com TECH SERVICE HOTLINE 800-537-3365