



# A510004

## Replacement Concrete Bolts for 10k Steel Mega-Swivel Concrete Anchorage Connector

### FEATURES

- Minimum Breaking Strength (MBS): 10,000 pounds
- Steel construction
- Fastener for 10K Mega-Swivel in concrete
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502 requirements
- Pack of 10



### SPECIFICATIONS

Model No.	Material	Mounting Hole Dia.	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A510004	Steel	3/4 in (19 mm)	10,000 lbs (44.4 kN)	2.0 lbs (0.91 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926

\*See User Instructions for more information.

**⚠ WARNING:** Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

# Technical Data Sheet