

3/4" DRIVE ONE PIECE IMPACT HEX BIT DRIVER, SAE Black Industrial Finish

| Product Code | Hex Size (Inches) | A | B | F | Uses RET RING® Number | Use O-Ring / Pin |
|--------------|----------------------|-------|-----------------------|----------------|--------------------------|---------------------|
| | | OAL | Drive End Diameter | Nose Length | | |
| 38216 | 1/2 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38218 | 9/16 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38220 | 5/8 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38224 | 3/4 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38226 | 13/16 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38228 | 7/8 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38232 | 1 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38236 | 1 1/8 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |
| 38240 | 1 1/4 | 3 1/2 | 1 3/4 | 3/4 | 6-1XS | 6-1A / 6-2C |

38932 5 Piece 3/4" Drive Hex-Driver Impact Socket Set on Clip Rail Contents Include:

| Product Code | Size (Inches) | Product Code | Size (Inches) |
|--------------|---------------|--------------|---------------|
| 38220 | 5/8 | 38228 | 7/8 |
| 38224 | 3/4 | 38232 | 1 |
| 38226 | 13/16 | | |

38903 9 Piece 3/4" Drive Hex-Driver Impact Socket Set with 50085 Metal Box Contents Include:

| Product Code | Size (Inches) | Product Code | Size (Inches) |
|--------------|---------------|--------------|---------------|
| 38216 | 1/2 | 38228 | 7/8 |
| 38218 | 9/16 | 38232 | 1 |
| 38220 | 5/8 | 38236 | 1 1/8 |
| 38224 | 3/4 | 38240 | 1 1/4 |
| 38226 | 13/16 | | |

Features

- One-piece design maximizes strength and reduces breakage.
- Chamfered ends provide easy engagement of the drive tool and fastener.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.

TOOLS@HEIGHT
DROP PREVENTION SYSTEM

Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



38240

38216



38932



38903